

FRESHWATER PH INDICATOR SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-4
Version No:6
CD 2010/1 Page 1 of 8

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

FRESHWATER PH INDICATOR SOLUTION

OTHER NAMES

"Solution ID# 3320"

PRODUCT USE


pH indicator solution for product 28.

SUPPLIER

Company: Mars Fishcare Inc
Address:
50 East Hamilton Street
Chalfont
PA, 18914
USA
Telephone: +1 215 822 8181
Fax: +1 215 822 1906

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS



EMERGENCY OVERVIEW

HAZARD

Not hazardous

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
non hazardous ingredients		100

continued...

FRESHWATER PH INDICATOR SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-4
Version No:6
CD 2010/1 Page 2 of 8

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with eyes:

- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered to be a significant fire risk.
- Expansion or decomposition on heating may lead to violent rupture of containers.
- Decomposes on heating and may produce toxic/ irritating fumes.
- May emit acrid smoke.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

PERSONAL PROTECTION

Glasses:
Chemical goggles.

Gloves:
When handling larger quantities:

continued...

FRESHWATER PH INDICATOR SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-4
Version No:6
CD 2010/1 Page 3 of 8

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- When handling DO NOT eat, drink or smoke.
- Always wash hands with soap and water after handling.
- Avoid physical damage to containers.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+ + + + X +

+: May be stored together

O: May be stored together with specific precautions

X: Must not be stored together

continued...

FRESHWATER PH INDICATOR SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-4
Version No:6
CD 2010/1 Page 4 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

MATERIAL DATA

FRESHWATER PH INDICATOR SOLUTION:
Not available

PERSONAL PROTECTION



EYE

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear general protective gloves, eg. light weight rubber gloves.

OTHER

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Barrier cream.
- Eyewash unit.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape"

continued...

FRESHWATER PH INDICATOR SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-4
Version No:6
CD 2010/1 Page 5 of 8

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air)	0.25- 0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Orange brown odourless liquid; mixes with water.

PHYSICAL PROPERTIES

Liquid.
Mixes with water.

continued...

FRESHWATER PH INDICATOR SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-4
Version No:6
CD 2010/1 Page 6 of 8

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°F)	Not Available	Viscosity	Not Available
Boiling Range (°F)	Not Available	Solubility in water (g/L)	Miscible
Flash Point (°F)	Not Applicable	pH (1% solution)	Not Available
Decomposition Temp (°F)	Not Available	pH (as supplied)	4.5- 5.8
Autoignition Temp (°F)	Not Applicable	Vapour Pressure (mmHG)	Not Available
Upper Explosive Limit (%)	Not Applicable	Specific Gravity (water=1)	0.997
Lower Explosive Limit (%)	Not Applicable	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available


Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
 - Product is considered stable.
 - Hazardous polymerisation will not occur.
- For incompatible materials - refer to Section 7 - Handling and Storage.*

Section 11 - TOXICOLOGICAL INFORMATION

CHEMWATCH HAZARD RATINGS



POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (eg. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure

continued...

FRESHWATER PH INDICATOR SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-4
Version No:6
CD 2010/1 Page 7 of 8

Section 11 - TOXICOLOGICAL INFORMATION

be kept to a minimum and that suitable gloves be used in an occupational setting.

INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

CHRONIC HEALTH EFFECTS

Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

Section 12 - ECOLOGICAL INFORMATION

No data

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle where possible
Otherwise ensure that:
- licenced contractors dispose of the product and its container.
- disposal occurs at a licenced facility.

Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

No data for Freshwater pH Indicator Solution (CW: 4650-4)

Section 16 - OTHER INFORMATION

CONTACT

Mars Fishcare

Classification of the preparation and its individual components has drawn on official and authoritative

continued...

FRESHWATER PH INDICATOR SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-4
Version No:6
CD 2010/1 Page 8 of 8
Section 16 - OTHER INFORMATION

sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following U.S. Regulations and Standards:

OSHA Standards - 29 CFR:
1910.132 - Personal Protective Equipment - General requirements
1910.133 - Eye and face protection
1910.134 - Respiratory Protection
1910.136 - Occupational foot protection
1910.138 - Hand Protection
Eye and face protection - ANSI Z87.1
Foot protection - ANSI Z41
Respirators must be NIOSH approved.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Dec-23-2009
Print Date: May-20-2010

HIGH RANGE PH TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-6
Version No:5
CD 2010/1 Page 1 of 9

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

HIGH RANGE PH TEST SOLUTION

OTHER NAMES

"Solution ID# 3339"

PRODUCT USE


pH test solution for product 27, 34 and 401M.

SUPPLIER

Company: Mars Fishcare Inc
Address:
50 East Hamilton Street
Chalfont
PA, 18914
USA
Telephone: +1 215 822 8181
Fax: +1 215 822 1906

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS



EMERGENCY OVERVIEW

HAZARD

Not hazardous

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
m- cresol purple	2303-01-7	N/S^

continued...

HIGH RANGE PH TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-6
Version No:5
CD 2010/1 Page 2 of 9

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with eyes:

- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

Treat symptomatically.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

FIRE/EXPLOSION HAZARD

- Non combustible.
- Not considered to be a significant fire risk.
- Expansion or decomposition on heating may lead to violent rupture of containers.
- Decomposes on heating and may produce toxic/ irritating fumes.
- May emit acrid smoke.

FIRE INCOMPATIBILITY

None known.

PERSONAL PROTECTION

Glasses:
Chemical goggles.

Gloves:
When handling larger quantities:

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.

continued...

HIGH RANGE PH TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-6
Version No:5
CD 2010/1 Page 3 of 9

Section 6 - ACCIDENTAL RELEASE MEASURES

- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Limit all unnecessary personal contact.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- When handling DO NOT eat, drink or smoke.
- Always wash hands with soap and water after handling.
- Avoid physical damage to containers.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.

SUITABLE CONTAINER

- Polyethylene or polypropylene container.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: *May be stored together*

O: *May be stored together with specific preventions*

X: *Must not be stored together*

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

US OSHA Permissible Exposure Levels (PELs)

continued...

HIGH RANGE PH TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-6
Version No:5
CD 2010/1 Page 4 of 9

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Z	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Max excursion ppm	Max excursion mg/m ³	Max excursion duration (mins)	TWA F/CC
Z3	Inert or Nuisance Dust: (d) Respirable fraction		5								
Z3	Inert or Nuisance Dust: (d) Total dust		15								

Source	Material	TWA ppm	TWA mg/m ³	Notes
US - California Permissible Exposure Limits for Chemical Contaminants	m- cresol purple (Cresol (all isomers))	5	22	
US OSHA Permissible Exposure Levels (PELs) - Table Z3	m- cresol purple (Inert or Nuisance Dust: (d) Respirable fraction)		5	
US OSHA Permissible Exposure Levels (PELs) - Table Z3	m- cresol purple (Inert or Nuisance Dust: (d) Total dust)		15	
US - Oregon Permissible Exposure Limits (Z3)	m- cresol purple (Inert or Nuisance Dust: (d) Total dust)		10	*
US - Hawaii Air Contaminant Limits	m- cresol purple (Particulates not otherwise regulated - Total dust)		10	
US - Hawaii Air Contaminant Limits	m- cresol purple (Particulates not otherwise regulated - Respirable fraction)		5	
US - Oregon Permissible Exposure Limits (Z3)	m- cresol purple (Inert or Nuisance Dust: (d) Respirable fraction)		5	*
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	m- cresol purple (Particulates not otherwise regulated Respirable fraction)		5	
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	m- cresol purple (Particulates not otherwise regulated (PNOR)(f)- Respirable fraction)		5	
US - Michigan Exposure Limits for Air Contaminants	m- cresol purple (Particulates not otherwise regulated, Respirable dust)		5	

MATERIAL DATA

HIGH RANGE PH TEST SOLUTION:

Not available

continued...

HIGH RANGE PH TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-6
Version No:5
CD 2010/1 Page 5 of 9

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION



EYE

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

Wear general protective gloves, eg. light weight rubber gloves.

OTHER

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Barrier cream.
- Eyewash unit.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:
solvent, vapours, degreasing etc., evaporating
from tank (in still air)

Air Speed:
0.25- 0.5 m/s (50- 100 f/min)

continued...

HIGH RANGE PH TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-6
Version No:5
CD 2010/1 Page 6 of 9

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Purple red solution with a mild odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.
Mixes with water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°F)	Not Available	Viscosity	Not Available
Boiling Range (°F)	Not Available	Solubility in water (g/L)	Miscible
Flash Point (°F)	Not Applicable	pH (1% solution)	Not Available
Decomposition Temp (°F)	Not Available	pH (as supplied)	7.6- 8.4
Autoignition Temp (°F)	Not Applicable	Vapour Pressure (mmHG)	Not Available
Upper Explosive Limit (%)	Not Applicable	Specific Gravity (water=1)	0.997 approx.

continued...

HIGH RANGE PH TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-6
Version No:5
CD 2010/1 Page 7 of 9

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Lower Explosive Limit (%)	Not Applicable	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION


CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

CHEMWATCH HAZARD RATINGS



POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (eg. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

continued...

HIGH RANGE PH TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-6
Version No:5
CD 2010/1 Page 8 of 9

Section 11 - TOXICOLOGICAL INFORMATION

CHRONIC HEALTH EFFECTS

Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

Section 12 - ECOLOGICAL INFORMATION

No data

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle where possible
Otherwise ensure that:
- licenced contractors dispose of the product and its container.
- disposal occurs at a licenced facility.

Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

No data for High Range pH Test Solution (CW: 4650-6)

Section 16 - OTHER INFORMATION

CONTACT

Mars Fishcare

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined

continued...

HIGH RANGE PH TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-6
Version No:5
CD 2010/1 Page 9 of 9
Section 16 - OTHER INFORMATION

by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following U.S. Regulations and Standards:

OSHA Standards - 29 CFR:

1910.132 - Personal Protective Equipment - General requirements

1910.133 - Eye and face protection

1910.134 - Respiratory Protection

1910.136 - Occupational foot protection

1910.138 - Hand Protection

Eye and face protection - ANSI Z87.1

Foot protection - ANSI Z41

Respirators must be NIOSH approved.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Dec-23-2009

Print Date: May-20-2010

LIQUID AMMONIA TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-12
Version No:5
CD 2010/1 Page 1 of 14

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

LIQUID AMMONIA TEST SOLUTION #1

OTHER NAMES

"Solution ID# 3335A"

PRODUCT USE


Ammonia test solution for product LR8600, 34 and 401M.

SUPPLIER

Company: Mars Fishcare Inc
Address:
50 East Hamilton Street
Chalfont
PA, 18914
USA
Telephone: +1 215 822 8181
Fax: +1 215 822 1906

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS



GHS Classification

Eye Irritation Category 2A
Reproductive Toxicity Category 1B
Respiratory Sensitizer Category 1
Skin Sensitizer Category 1



continued...

LIQUID AMMONIA TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-12
Version No:5
CD 2010/1 Page 2 of 14
Section 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by Chemwatch using GHS criteria:

H319 H334 H317 H360

Causes serious eye irritation

May cause allergic or asthmatic symptoms or breathing difficulties if inhaled

May cause allergic skin reaction

May damage the unborn child

PRECAUTIONARY STATEMENTS

Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

In case of inadequate ventilation wear respiratory protection.

Response

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/ attention.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Wash contaminated clothing before reuse.

Storage

Store locked up.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
polyethylene glycol	25322-68-3	<90
sodium salicylate	54-21-7	<10

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

continued...

LIQUID AMMONIA TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-12
Version No:5
CD 2010/1 Page 3 of 14
Section 4 - FIRST AID MEASURES

- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin contact occurs:

- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

Treat symptomatically.

for salicylate intoxication:

- Pending gastric lavage, use emetics such as syrup of Ipecac or delay gastric emptying and absorption by swallowing a slurry of activated charcoal. Do not give ipecac after charcoal.
- Gastric lavage with water or perhaps sodium bicarbonate solution (3%-5%). Mild alkali delays salicylate absorption from the stomach and perhaps slightly from the duodenum.
- Saline catharsis with sodium or magnesium sulfate (15-30 gm in water).
- Take an immediate blood sample for an appraisal of the patient's acid-base status. A pH determination on an anaerobic sample of arterial blood is best. An analysis of the plasma salicylate concentration should be made at the same time. Laboratory controls are almost essential for the proper management of severe salicylism.
- In the presence of an established acidosis, alkali therapy is essential, but at least in an adult, alkali should be withheld until its need is demonstrated by chemical analysis. The intensity of treatment depends on the intensity of acidosis. In the presence of vomiting, intravenous sodium bicarbonate is the most satisfactory of all alkali therapy.
- Correct dehydration and hypoglycaemia (if present) by the intravenous administration of glucose in water or in isotonic saline. The administration of glucose may also serve to remedy ketosis which is often seen in poisoned children.
- Even in patients without hypoglycaemia, infusions of glucose adequate to produce distinct hyperglycaemia are recommended to prevent glucose depletion in the brain. This recommendation is based on impressive experimental data in animals.
- Renal function should be supported by correcting dehydration and incipient shock. Overhydration is not justified. An alkaline urine should be maintained by the administration of alkali if necessary with care to prevent a severe systemic alkalosis. As long as urine remains alkaline (pH above 7.5), administration of an osmotic diuretic such as mannitol or perhaps THAM is useful, but one must be careful to avoid hypokalaemia. Supplements of potassium chloride should be included in parenteral fluids.
- Small doses of barbiturates, diazepam, paraldehyde, or perhaps other sedatives (but probably not morphine) may be required to suppress extreme restlessness and convulsions.
- For hyperpyrexia, use sponge baths.

continued...

LIQUID AMMONIA TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-12
Version No:5
CD 2010/1 Page 4 of 14
Section 4 - FIRST AID MEASURES

The presence of petechiae or other signs of haemorrhagic tendency calls for a large Vitamin K dose and perhaps ascorbic acid. Minor transfusions may be necessary since bleeding in salicylism is not always due to a prothrombin effect.

- Haemodialysis and haemoperfusion have proved useful in salicylate poisoning, as have peritoneal dialysis and exchange transfusions, but alkaline diuretic therapy is probably sufficient except in fulminating cases.

[GOSSELIN, et.al.: Clinical Toxicology of Commercial Products]

The mechanism of the toxic effect involves metabolic acidosis, respiratory alkalosis, hypoglycaemia, and potassium depletion. Salicylate poisoning is characterised by extreme acid-base disturbances, electrolyte disturbances and decreased levels of consciousness. There are differences between acute and chronic toxicity and a varying clinical picture which is dependent on the age of the patient and their kidney function. The major feature of poisoning is metabolic acidosis due to "uncoupling of oxidative phosphorylation" which produces an increased metabolic rate, increased oxygen consumption, increased formation of carbon dioxide, increased heat production and increased utilisation of glucose. Direct stimulation of the respiratory centre leads to hyperventilation and respiratory alkalosis. This leads to compensatory increased renal excretion of bicarbonate which contributes to the metabolic acidosis which may coexist or develop subsequently. Hypoglycaemia may occur as a result of increased glucose demand, increased rates of tissue glycolysis, and impaired rate of glucose synthesis. NOTE: Tissue glucose levels may be lower than plasma levels. Hyperglycaemia may occur due to increased glycogenolysis. Potassium depletion occurs as a result of increased renal excretion as well as intracellular movement of potassium.

Salicylates competitively inhibit vitamin K dependent synthesis of factors II, VII, IX, X and in addition, may produce a mild dose dependent hepatitis. Salicylates are bound to albumin. The extent of protein binding is concentration dependent (and falls with higher blood levels). This, and the effects of acidosis, decreasing ionisation, means that the volume of distribution increases markedly in overdose as does CNS penetration. The extent of protein binding (50-80%) and the rate of metabolism are concentration dependent. Hepatic clearance has zero order kinetics and thus the therapeutic half-life of 2-4.5 hours but the half-life in overdose is 18-36 hours. Renal excretion is the most important route in overdose. Thus when the salicylate concentrations are in the toxic range there is increased tissue distribution and impaired clearance of the drug.

HyperTox 3.0 <http://www.ozemail.com.au/~ouad/SALI0001.HTA>.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE/EXPLOSION HAZARD

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Combustion products include: carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

continued...

LIQUID AMMONIA TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-12
Version No:5
CD 2010/1 Page 5 of 14
Section 5 - FIRE FIGHTING MEASURES

May emit corrosive fumes.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

PERSONAL PROTECTION

Glasses:
Safety Glasses.

Gloves:
PVC chemical resistant type.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- DO NOT allow clothing wet with material to stay in contact with skin.
- DO NOT USE brass or copper containers / stirrers.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

continued...

LIQUID AMMONIA TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Dec-23-2009
 NC614TDP

CHEMWATCH 4650-12
 Version No:5
 CD 2010/1 Page 6 of 14
 Section 7 - HANDLING AND STORAGE

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+ X + X X +

- +: May be stored together
 O: May be stored together with specific preventions
 X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

US OSHA Permissible Exposure Levels (PELs)

Z	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Max excursion ppm	Max excursion mg/m ³	Max excursion duration (mins)	TWA F/CC
Z3	Inert or Nuisance Dust: (d) Respirable fraction		5								
Z3	Inert or Nuisance Dust: (d) Total dust		15								

Source	Material	TWA mg/m ³	Notes
US - Oregon Permissible Exposure Limits (Z3)	polyethylene glycol (Inert or Nuisance Dust: (d) Total dust)	10	*
US OSHA Permissible Exposure Levels (PELs) - Table Z3	polyethylene glycol (Inert or Nuisance Dust: (d) Respirable fraction)	5	
US OSHA Permissible Exposure Levels (PELs) - Table Z3	polyethylene glycol (Inert or Nuisance Dust: (d) Total dust)	15	
US - Hawaii Air Contaminant Limits	polyethylene glycol (Particulates not other wise regulated - Total dust)	10	
US - Hawaii Air Contaminant Limits	polyethylene glycol (Particulates not other wise regulated - Respirable fraction)	5	

continued...

LIQUID AMMONIA TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-12
Version No:5
CD 2010/1 Page 7 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA mg/m ³	Notes
US - Oregon Permissible Exposure Limits (Z3)	polyethylene glycol (Inert or Nuisance Dust: (d) Respirable fraction)	5	*
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	polyethylene glycol (Particulates not otherwise regulated Respirable fraction)	5	
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	polyethylene glycol (Particulates not otherwise regulated (PNOR)(f)- Respirable fraction)	5	
US - Michigan Exposure Limits for Air Contaminants	polyethylene glycol (Particulates not otherwise regulated, Respirable dust)	5	

The following materials had no OELs on our records

- sodium salicylate:

CAS:54- 21- 7

MATERIAL DATA

LIQUID AMMONIA TEST SOLUTION #1:

Not available

POLYETHYLENE GLYCOL:

For powdered forms:

The polyethylene glycols are extremely low in oral toxicity, are not significantly irritating to the eyes or skin, and are not absorbed through the skin in toxic amounts. vapour pressures are extremely low and inhalation exposure is limited to mists. Based on experimental data and human experience, these substances do not present significant hazards to health in the workplace.

SODIUM SALICYLATE:

It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.

At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal experiments or clinical experience). Airborne concentrations must be maintained as low as is practically possible and occupational exposure must be kept to a minimum.

NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be

continued...

LIQUID AMMONIA TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-12
Version No:5
CD 2010/1 Page 8 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION


consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

CEL TWA: 5 mg/m³ [as analogue for aspirin]

PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber.

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:
 - frequency and duration of contact,
 - chemical resistance of glove material,
 - glove thickness and
 - dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

continued...

LIQUID AMMONIA TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-12
Version No:5
CD 2010/1 Page 9 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank (in still air)	Air Speed: 0.25- 0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in

continued...

LIQUID AMMONIA TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-12
Version No:5
CD 2010/1 Page 10 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Reddish-orange liquid with a mild odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.
Mixes with water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°F)	Not Available	Viscosity	Not Available
Boiling Range (°F)	Not Available	Solubility in water (g/L)	Miscible
Flash Point (°F)	Not Applicable	pH (1% solution)	Not Available
Decomposition Temp (°F)	Not Available	pH (as supplied)	8.3
Autoignition Temp (°F)	Not Applicable	Vapour Pressure (mmHG)	Not Available
Upper Explosive Limit (%)	Not Applicable	Specific Gravity (water=1)	1.152
Lower Explosive Limit (%)	Not Applicable	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION


CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

CHEMWATCH HAZARD RATINGS



continued...

LIQUID AMMONIA TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-12
Version No:5
CD 2010/1 Page 11 of 14
Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

Accidental ingestion of the material may be damaging to the health of the individual.

High oral doses of salicylates, such as aspirin, may cause a mild burning pain in the throat and stomach, causing vomiting. This is followed (within hours) by deep, rapid breathing, tiredness, nausea and further vomiting, thirst and diarrhoea. The central nervous system is first stimulated, and then depression from failure occurs. Stimulation produces vomiting, hyperventilation, headache, ringing in the ears, confusion, behaviour and mood changes, and generalised convulsions. Respiratory failure and cardiovascular collapse can result in death. There may also be sweating, skin eruptions, internal bleeding, kidney failure and inflamed pancreas. There may be bloody stools, purple skin spots or blood in the vomit. Many of these symptoms are due to disturbances in blood chemistry. A dose of 300 mg/kg can cause serious effects while 500 mg/kg can be lethal.

EYE

This material can cause eye irritation and damage in some persons.

Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Not normally a hazard due to non-volatile nature of product.

Inhalation hazard is increased at higher temperatures.

CHRONIC HEALTH EFFECTS

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby.

Chronic exposure to salicylates produce problems with metabolism, central nervous system disturbances, or kidney damage. Those with pre-existing damage to the eye, skin or kidney are especially at risk.

Hypersensitive reactions can occur, especially in people with asthma. These symptoms include itchy wheals and other skin eruptions, an inflamed nose, shortness of breath and serious narrowing of the airways (which can even cause death). Chronic exposure to parabens by skin contact, ingestion or injection can cause hypersensitive reactions. There may be cross-sensitivity between different species, so people can develop allergic symptoms if they were sensitised by other chemicals. Symptoms include acute narrowing of the airways, hives (itchy wheal), swelling, running nose and blurred vision. There may be anaphylactic shock and rash.

continued...

LIQUID AMMONIA TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-12
Version No:5
CD 2010/1 Page 12 of 14
Section 11 - TOXICOLOGICAL INFORMATION

TOXICITY AND IRRITATION

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

POLYETHYLENE GLYCOL:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 33750 mg/kg

for molecular weights (200-8000) *

Oral (rat) LD50: 31000->50000 mg/kg

Oral (mice) LD50: 38000->50000 mg/kg

Oral (g.pig) LD50: 17000->50000 mg/kg

Oral (rabbit) LD50: 14000->50000 mg/kg

Intraperitoneal (mice) LD50: 3100-12900 mg/kg

IRRITATION

Skin (rabbit): 500mg/24h - mild.

Eye (rabbit): 500mg/24h - mild.

* AIHA WEEL Guides

SODIUM SALICYLATE:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (human) LDLo: 700 mg/kg

Oral (rat) LD50: 1200 mg/kg

Intraperitoneal (rat) LD50: 542 mg/kg

Subcutaneous (rat) LD50: 980 mg/kg

IRRITATION

Nil Reported

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

SODIUM SALICYLATE:

LIQUID AMMONIA TEST SOLUTION #1:

continued...

LIQUID AMMONIA TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-12
Version No:5
CD 2010/1 Page 13 of 14
Section 12 - ECOLOGICAL INFORMATION

DO NOT discharge into sewer or waterways.

LIQUID AMMONIA TEST SOLUTION #1:

POLYETHYLENE GLYCOL:

BOD 5 if unstated: 0-0.02,1%

COD: 1.62-1.74,98%

Toxicity Fish: TLm(96)>10000mg/L

SODIUM SALICYLATE:

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
polyethylene glycol	LOW		LOW	HIGH
sodium salicylate	LOW		LOW	HIGH

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle where possible
Otherwise ensure that:
- licenced contractors dispose of the product and its container.
- disposal occurs at a licenced facility.

Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

Regulations for ingredients

polyethylene glycol (CAS: 25322-68-3) is found on the following regulatory lists;

"GESAMP/EHS Composite List - GESAMP Hazard Profiles"; "IMO IBC Code Chapter 17: Summary of minimum requirements"; "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances"; "US - Minnesota Hazardous Substance List"; "US Cosmetic Ingredient Review (CIR) Cosmetic ingredients found safe, with qualifications"; "US DOE Temporary Emergency Exposure Limits (TEELs)"; "US DOT Coast Guard Bulk Hazardous Materials - List of Flammable and Combustible Bulk Liquid Cargoes"; "US EPA High Production Volume Program Chemical List"; "US FDA Indirect Food Additives: Adhesives and Components of Coatings - Substances for Use Only as Components of Adhesives - Adhesives"; "US Food Additive Database"; "US Inventory of Effective Food Contact Substance Notifications"; "US Toxic Substances Control Act (TSCA) - Inventory"

sodium salicylate (CAS: 54-21-7) is found on the following regulatory lists;

"Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)"; "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (French)"; "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances"; "US Cosmetic Ingredient Review (CIR) Cosmetic ingredients found safe, with qualifications"; "US DOE Temporary Emergency Exposure Limits (TEELs)"; "US EPA High Production Volume Program Chemical List"; "US FDA Indirect Food Additives: Adhesives and Components of Coatings - Substances for Use Only as Components of Adhesives - Adhesives"; "US Inventory of Effective Food Contact Substance Notifications"; "US Toxic Substances Control Act (TSCA) - Inventory"

No data for Liquid Ammonia Test Solution #1 (CW: 4650-12)

continued...

LIQUID AMMONIA TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-12
Version No:5
CD 2010/1 Page 14 of 14

Section 16 - OTHER INFORMATION

EXPOSURE STANDARD FOR MIXTURES

"Worst Case" computer-aided prediction of spray/ mist or fume/ dust components and concentration:

Composite Exposure Standard for Mixture (TWA) :5 mg/m³.

Operations which produce a spray/mist or fume/dust, introduce particulates to the breathing zone.

If the breathing zone concentration of ANY of the components listed below is exceeded, "Worst Case" considerations deem the individual to be overexposed.

Component Breathing Zone ppm Breathing Zone mg/m³ Mixture Conc (%).

Component Mixture Conc (%)	Breathing zone (ppm) sodium salicylate	Breathing zone (mg/m ³) 5.0000
10.0		

CONTACT

Mars Fishcare

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following U.S. Regulations and Standards:

OSHA Standards - 29 CFR:

1910.132 - Personal Protective Equipment - General requirements

1910.133 - Eye and face protection

1910.134 - Respiratory Protection

1910.136 - Occupational foot protection

1910.138 - Hand Protection

Eye and face protection - ANSI Z87.1

Foot protection - ANSI Z41

Respirators must be NIOSH approved.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Dec-23-2009

Print Date: May-20-2010

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 1 of 24

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

LIQUID AMMONIA TEST SOLUTION #2

OTHER NAMES

"Solution ID# 3335B"

PROPER SHIPPING NAME

CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.(Contains sodium hydroxide, sodium hypochlorite)

PRODUCT USE


Ammonia test solution for product LR8600, 34 and 401M.

SUPPLIER

Company: Mars Fishcare Inc
Address:
50 East Hamilton Street
Chalfont
PA, 18914
USA
Telephone: +1 215 822 8181
Fax: +1 215 822 1906

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS



GHS Classification

Acute Aquatic Hazard Category 3
Metal Corrosion Category 1
Serious Eye Damage Category 1
Skin Corrosion/Irritation Category 1B



continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 2 of 24
Section 2 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by Chemwatch using GHS criteria:

H290 H314 H318 H402

May be corrosive to metals

Causes severe skin burns and eye damage

Causes serious eye damage

Harmful to aquatic life

PRECAUTIONARY STATEMENTS

Prevention

Keep only in original container.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Storage

Store locked up.

Store in corrosive resistant container or with a resistant inner liner.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
sodium hydroxide	1310-73-2	<10
sodium hypochlorite	7681-52-9	<1

Section 4 - FIRST AID MEASURES

SWALLOWED

- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 3 of 24
Section 4 - FIRST AID MEASURES

- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Transport to hospital or doctor without delay.

EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin or hair contact occurs:

- Immediately flush body and clothes with large amounts of water, using safety shower if available.
- Quickly remove all contaminated clothing, including footwear.
- Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.
- Transport to hospital, or doctor.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

For acute or short-term repeated exposures to highly alkaline materials:

- Respiratory stress is uncommon but present occasionally because of soft tissue edema.
- Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.
- Oxygen is given as indicated.
- The presence of shock suggests perforation and mandates an intravenous line and fluid administration.
- Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.

Alkalis continue to cause damage after exposure.

INGESTION:

- Milk and water are the preferred diluents

No more than 2 glasses of water should be given to an adult.

- Neutralising agents should never be given since exothermic heat reaction may compound injury.

* Catharsis and emesis are absolutely contra-indicated.

* Activated charcoal does not absorb alkali.

* Gastric lavage should not be used.

Supportive care involves the following:

- Withhold oral feedings initially.
- If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.
- Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia).

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 4 of 24
Section 4 - FIRST AID MEASURES

SKIN AND EYE:

- Injury should be irrigated for 20-30 minutes.
- Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE/EXPLOSION HAZARD

- Non combustible.
 - Not considered a significant fire risk, however containers may burn.
- May emit corrosive fumes.

FIRE INCOMPATIBILITY

None known.

Personal Protective Equipment

Gas tight chemical resistant suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

ACUTE EXPOSURE GUIDELINE LEVELS (AEGL) (in ppm)

sodium
hypochlori
te

AEGL Type	10 min	30 min	60 min	4 hr	8 hr
AEGL 1	0.5	0.5	0.5	0.5	GALSYN~
AEGL 2	2.8	2.8	2	1	GALSYN~
AEGL 3	50	28	20	10	GALSYN~

AEGL 1: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience notable discomfort, irritation, or certain asymptomatic nonsensory effects. However, the effects are not disabling and are transient and reversible upon cessation of exposure.

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 5 of 24

Section 6 - ACCIDENTAL RELEASE MEASURES

AEGL 2: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience irreversible or other serious, long-lasting adverse health effects or an impaired ability to escape.

AEGL 3: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience life-threatening health effects or death.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- **WARNING:** To avoid violent reaction, ALWAYS add material to water and NEVER water to material.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
- DO NOT allow clothing wet with material to stay in contact with skin.

SUITABLE CONTAINER

- Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polyliner drum.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

For low viscosity materials

- Drums and jerricans must be of the non-removable head type.
- Where a can is to be used as an inner package, the can must have a screwed enclosure.

For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):

- Removable head packaging;
 - Cans with friction closures and
 - low pressure tubes and cartridges
- may be used.

-

Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Dec-23-2009
 NC614TDP

CHEMWATCH 4650-9
 Version No:4
 CD 2010/1 Page 6 of 24
 Section 7 - HANDLING AND STORAGE

- Store away from incompatible materials and foodstuff containers.
 - Protect containers against physical damage and check regularly for leaks.
 - Observe manufacturer's storing and handling recommendations.
 - DO NOT store near acids, or oxidising agents.
- Protect containers against physical damage.
- Check regularly for spills and leaks.
 - No smoking, naked lights, heat or ignition sources.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



- +: May be stored together
 O: May be stored together with specific precautions
 X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

US OSHA Permissible Exposure Levels (PELs)

Z	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Max excursion ppm	Max excursion mg/m ³	Max excursion duration (mins)	TWA F/CC
Z1	Sodium hydroxide		2								
Z1	Chlorine					1	3				

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Notes
Canada - British Columbia Occupational Exposure Limits	sodium hydroxide (Sodium hydroxide)						2	
Canada - Ontario Occupational Exposure Limits	sodium hydroxide (Sodium hydroxide)						2	
US - Minnesota Permissible Exposure Limits (PELs)	sodium hydroxide (Sodium hydroxide)						2	

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Dec-23-2009
 NC614TDP

CHEMWATCH 4650-9
 Version No:4
 CD 2010/1 Page 7 of 24

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Notes
US ACGIH Threshold Limit Values (TLV)	sodium hydroxide (Sodium hydroxide)						2	TLV Basis: upper respiratory tract, eye & skin irritation
US NIOSH Recommended Exposure Limits (RELs)	sodium hydroxide (Sodium hydroxide)						2	
Canada - Alberta Occupational Exposure Limits	sodium hydroxide (Sodium hydroxide)						2	
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	sodium hydroxide (Sodium hydroxide)						2	
US - Vermont Permissible Exposure Limits Table Z- 1- A Transitional Limits for Air Contaminants	sodium hydroxide (Sodium hydroxide)		2					
US - Vermont Permissible Exposure Limits Table Z- 1- A Final Rule Limits for Air Contaminants	sodium hydroxide (Sodium hydroxide)						2	
US - California Permissible Exposure Limits for Chemical Contaminants	sodium hydroxide (Sodium hydroxide; caustic soda)						2	
US - Idaho - Limits for Air Contaminants	sodium hydroxide (Sodium hydroxide)		2					
US OSHA Permissible Exposure Levels (PELs) - Table Z1	sodium hydroxide (Sodium hydroxide)		2					
US - Hawaii Air Contaminant Limits	sodium hydroxide (Sodium hydroxide)						2	

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Dec-23-2009
 NC614TDP

CHEMWATCH 4650-9
 Version No:4
 CD 2010/1 Page 8 of 24

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Notes
US - Alaska Limits for Air Contaminants	sodium hydroxide (Sodium hydroxide)						2	
US - Michigan Exposure Limits for Air Contaminants	sodium hydroxide (Sodium hydroxide)						2	
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	sodium hydroxide (Sodium hydroxide)	-	2	-	-			
US - Washington Permissible exposure limits of air contaminants	sodium hydroxide (Sodium hydroxide)						2	
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	sodium hydroxide (Sodium hydroxide)						2	
Canada - Prince Edward Island Occupational Exposure Limits	sodium hydroxide (Sodium hydroxide)						2	TLV Basis: upper respiratory tract, eye & skin irritation
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	sodium hydroxide (Sodium hydroxide)		2					
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	sodium hydroxide (Sodium hydroxide)						2	
US - Oregon Permissible Exposure Limits (Z1)	sodium hydroxide (Sodium hydroxide)		2					

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Dec-23-2009
 NC614TDP

CHEMWATCH 4650-9
 Version No:4
 CD 2010/1 Page 9 of 24

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Notes
Canada - Northwest Territories Occupational Exposure Limits (English)	sodium hydroxide (Sodium hydroxide)						2	
Canada - Nova Scotia Occupational Exposure Limits	sodium hydroxide (Sodium hydroxide)						2	TLV Basis: upper respiratory tract, eye & skin irritation
US AIHA Workplace Environmental Exposure Levels (WEELs)	sodium hypochlorite (Sodium Hypochlorite)				2			
US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)	sodium hypochlorite (CHLORINE)	0.07						
US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)	sodium hypochlorite (CHLORINE)	0.002						
US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)	sodium hypochlorite (CHLORINE)	0.00005						
US - Minnesota Permissible Exposure Limits (PELs)	sodium hypochlorite (Chlorine)	0.5	1.5	1	3			
Canada - Alberta Occupational Exposure Limits	sodium hypochlorite (Chlorine)	0.5	1.5	1	2.9			
Canada - British Columbia Occupational Exposure Limits	sodium hypochlorite (Chlorine)	0.5		1				
Canada - Ontario Occupational Exposure Limits	sodium hypochlorite (Chlorine)	0.5		1				
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	sodium hypochlorite (Chlorine)	0.5	1.5	1	3			

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Dec-23-2009
 NC614TDP

CHEMWATCH 4650-9
 Version No:4
 CD 2010/1 Page 10 of 24

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Notes
US - Vermont Permissible Exposure Limits Table Z- 1- A Transitional Limits for Air Contaminants	sodium hypochlorite (Chlorine)	(C)1	(C)3					
US - Vermont Permissible Exposure Limits Table Z- 1- A Final Rule Limits for Air Contaminants	sodium hypochlorite (Chlorine)	0.5	1.5	1	3			
US - Idaho - Limits for Air Contaminants	sodium hypochlorite (Chlorine)					1	3	
US - California Permissible Exposure Limits for Chemical Contaminants	sodium hypochlorite (Chlorine)	0.5	1.5	1	3			
US NIOSH Recommended Exposure Limits (RELs)	sodium hypochlorite (Chlorine)					0.5	1.45	
US - Alaska Limits for Air Contaminants	sodium hypochlorite (Chlorine)	0.5	1.5	1	3			
US - Michigan Exposure Limits for Air Contaminants	sodium hypochlorite (Chlorine)	0.5	1.5	1	3			
US - Oregon Permissible Exposure Limits (Z1)	sodium hypochlorite (Chlorine)					1	3	
US - Hawaii Air Contaminant Limits	sodium hypochlorite (Chlorine)	0.5	1.5	1	3			
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	sodium hypochlorite (Chlorine)	1	3	3	9			

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Dec-23-2009
 NC614TDP

CHEMWATCH 4650-9
 Version No:4
 CD 2010/1 Page 11 of 24

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Notes
US - Washington Permissible exposure limits of air contaminants	sodium hypochlorite (Chlorine)	0.5				1		
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	sodium hypochlorite (Chlorine)	0.5		1				
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	sodium hypochlorite (Chlorine)	0.5	1.5	1	2.9			
US OSHA Permissible Exposure Levels (PELs) - Table Z1	sodium hypochlorite (Chlorine)					1	3	
US ACGIH Threshold Limit Values (TLV)	sodium hypochlorite (Chlorine)	0.5		1				TLV Basis: upper respiratory tract & eye irritation
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	sodium hypochlorite (Chlorine)					1	3	
Canada - Northwest Territories Occupational Exposure Limits (English)	sodium hypochlorite (Chlorine)	1	3	3	8.7	3	8.7	
Canada - Nova Scotia Occupational Exposure Limits	sodium hypochlorite (Chlorine)	0.5		1				TLV Basis: upper respiratory tract & eye irritation

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Dec-23-2009
 NC614TDP

CHEMWATCH 4650-9
 Version No:4
 CD 2010/1 Page 12 of 24

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Notes
Canada - Prince Edward Island Occupational Exposure Limits	sodium hypochlorite (Chlorine)	0.5		1				TLV Basis: upper respiratory tract & eye irritation

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
sodium hydroxide	10	
sodium hypochlorite		10

MATERIAL DATA

LIQUID AMMONIA TEST SOLUTION #2:

Not available

SODIUM HYDROXIDE:

for sodium hydroxide:

The TLV-C is recommended based on concentrations that produce noticeable but not excessive, ocular and upper respiratory tract irritation.

SODIUM HYPOCHLORITE:

Odour Threshold Value: 0.08 ppm (detection) - olfactory fatigue may develop

NOTE: Detector tubes for chlorine, measuring in excess of 0.2 ppm, are commercially available. Long-term measurements (8 hrs) may be conducted to detect concentrations exceeding 0.13 ppm.

Smell is not a good indicator of severity of exposure in the range 0.5 to 2 ppm. In this range subjects found exposure unpleasant with itching and burning of the throat reported and occasionally an urge to cough. Significant differences in the responses of males and females were also recorded with females often reporting headache and drowsiness.

Exposure at 1 ppm chlorine for 8 hours produced significant changes in pulmonary function and increased subjective irritation. Similar 8 hour exposures at 0.5 ppm produced no significant pulmonary function changes and less severe subjective irritation. Exposures for 2 hours at 2 ppm chlorine produced no significant changes in pulmonary irritation.

An 8 hour exposure at 1.5 ppm produced increased mucous secretion from the nose and increased mucous in the hypopharynx. Exposure at or below the TLV-TWA and STEL is thought to protect the worker against annoying symptoms in nose, throat and conjunctiva and declines in pulmonary function.

Odour Safety Factor(OSF)

OSF=1.6 (CHLORINE).

available chlorine, as chlorine

TLV TWA: 0.5 ppm, 1.5 mg/m³: STEL: 1 ppm, 2.9 mg/m³

ES Peak: 1 ppm, 3 mg/m³

CEL TWA: 2 mg/m³ (compare WEEL TWA)

The odour threshold is likely to be similar to that of chlorine, 0.3 ppm.

Acute, subchronic, and chronic toxicity studies have shown no significant treatment related effects. High concentrations may produce moderate to severe eye irritation, but not permanent injury. High doses also appear to be embryotoxic. Since nearly all sodium hypochlorite is handled as aqueous solution, airborne exposure is likely to be as an aerosol, or mist. Sodium hypochlorite dissociates in water to form free

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 13 of 24

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

hypochlorous acid in equilibrium. The toxic effects are likely to be similar to those of chlorine or sodium hydroxide.

PERSONAL PROTECTION



EYE

- Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure
- Chemical goggles whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted
- Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.
- Alternatively a gas mask may replace splash goggles and face shields.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

- Elbow length PVC gloves.
- When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	B- P- - AUS	-
1000	50	-	B- P- - AUS
5000	50	Airline *	-

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 14 of 24

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

5000	100	-	B- P- - 2
10000	100	-	B- P- - 3
	100+		Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant:	Air Speed:
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25- 0.5 m/s (50- 100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 15 of 24

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Clear alkaline liquid with a chlorine odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.
Mixes with water.
Corrosive.
Alkaline.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°F)	Not Available	Viscosity	Not Available
Boiling Range (°F)	Not Available	Solubility in water (g/L)	Miscible
Flash Point (°F)	Not Applicable	pH (1% solution)	Not Available
Decomposition Temp (°F)	Not Available	pH (as supplied)	13.3- 13.9
Autoignition Temp (°F)	Not Applicable	Vapour Pressure (mmHG)	Not Available
Upper Explosive Limit (%)	Not Applicable	Specific Gravity (water=1)	1.099
Lower Explosive Limit (%)	Not Applicable	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION


CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

CHEMWATCH HAZARD RATINGS



continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 16 of 24
Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

The material can produce severe chemical burns within the oral cavity and gastrointestinal tract following ingestion.

Ingestion of alkaline corrosives may produce burns around the mouth, ulcerations and swellings of the mucous membranes, profuse saliva production, with an inability to speak or swallow. Both the oesophagus and stomach may experience burning pain; vomiting and diarrhoea may follow. Epiglottal swelling may result in respiratory distress and asphyxia; shock can occur. Narrowing of the oesophagus, stomach or stomach valve may occur immediately or after a long delay (weeks to years). Severe exposure can perforate the oesophagus or stomach leading to infections of the chest or abdominal cavity, with low chest pain, abdominal stiffness and fever. All of the above can cause death.

EYE

The material can produce severe chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating.

If applied to the eyes, this material causes severe eye damage.

Direct eye contact with corrosive bases can cause pain and burns. There may be swelling, epithelium destruction, clouding of the cornea and inflammation of the iris. Mild cases often resolve; severe cases can be prolonged with complications such as persistent swelling, scarring, permanent cloudiness, bulging of the eye, cataracts, eyelids glued to the eyeball and blindness.

SKIN

The material can produce severe chemical burns following direct contact with the skin.

Skin contact with alkaline corrosives may produce severe pain and burns; brownish stains may develop. The corroded area may be soft, gelatinous and necrotic; tissue destruction may be deep.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

If inhaled, this material can irritate the throat and lungs of some persons.

Inhaling corrosive bases may irritate the respiratory tract. Symptoms include cough, choking, pain and damage to the mucous membrane. In severe cases, lung swelling may develop, sometimes after a delay of hours to days. There may be low blood pressure, a weak and rapid pulse, and crackling sounds.

CHRONIC HEALTH EFFECTS

Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Gastrointestinal disturbances may also occur. Chronic exposures may result in dermatitis and/or conjunctivitis.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

SODIUM HYDROXIDE:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

IRRITATION

Skin (rabbit): 500 mg/24h SEVERE

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 17 of 24
Section 11 - TOXICOLOGICAL INFORMATION

Eye (rabbit): 0.05 mg/24h SEVERE
Eye (rabbit):1 mg/24h SEVERE
Eye (rabbit):1 mg/30s rinsed- SEVERE

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.

SODIUM HYPOCHLORITE:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (mouse) LD50: 5800 mg/kg
Oral (woman) TDLo: 1000 mg/kg
Oral (rat) LD50: 8910 mg/kg

IRRITATION

Eye (rabbit): 10 mg - Moderate
Skin (rabbit): 500 mg/24h- Moderate
Eye (rabbit): 100 mg - Moderate

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. Hypochlorite salts are classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing. The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. Hypochlorite salts are extremely corrosive and can cause severe damage to the eyes and skin. A number of fibrosarcomas and squamous cell carcinomas were observed in mice treated dermally with repeated subcarcinogenic doses of 4-nitroquinoline-1-oxide, followed by dermal treatment with sodium hypochlorite. as sodium hypochlorite pentahydrate

CARCINOGEN

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 18 of 24

Section 11 - TOXICOLOGICAL INFORMATION

Hypochlorite salts	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3
Chlorine	US ACGIH Threshold Limit Values (TLV) - Carcinogens	Carcinogen Category	A4
BROMINE COMPOUNDS (ORGANIC OR INORGANIC)	US Environmental Defense Scorecard Suspected Carcinogens	Reference(s)	P65- MC
SKIN			
sodium hydroxide	US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs) - Skin	Skin	X
sodium hydroxide	US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs) - Skin	Skin	X
sodium hydroxide	US - Vermont Permissible Exposure Limits Table Z- 1- A Transitional Limits for Air Contaminants - Skin	Skin Designation	X
sodium hydroxide	US - Washington Permissible exposure limits of air contaminants - Skin	Skin	X
sodium hydroxide	US - Hawaii Air Contaminant Limits - Skin Designation	Skin Designation	X
sodium hydroxide	US - California Permissible Exposure Limits for Chemical Contaminants - Skin	Skin	X

Section 12 - ECOLOGICAL INFORMATION

sodium hypochlorite 48 hr EC50 (56.4) mg/L Daggerblade grass shrimp Crustacea Source:

Refer to data for ingredients, which follows:

SODIUM HYDROXIDE:

SODIUM HYPOCHLORITE:

LIQUID AMMONIA TEST SOLUTION #2:

DO NOT discharge into sewer or waterways.

Prevent, by any means available, spillage from entering drains or water courses.

LIQUID AMMONIA TEST SOLUTION #2:

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 19 of 24
Section 12 - ECOLOGICAL INFORMATION

Marine Pollutant: Not Determined

Harmful to aquatic organisms.

SODIUM HYDROXIDE:

Metal-containing inorganic substances generally have negligible vapour pressure and are not expected to partition to air. Once released to surface waters and moist soils their fate depends on solubility and dissociation in water. Environmental processes (such as oxidation and the presence of acids or bases) may transform insoluble metals to more soluble ionic forms. Microbiological processes may also transform insoluble metals to more soluble forms. Such ionic species may bind to dissolved ligands or sorb to solid particles in aquatic or aqueous media. A significant proportion of dissolved/ sorbed metals will end up in sediments through the settling of suspended particles. The remaining metal ions can then be taken up by aquatic organisms.

When released to dry soil most metals will exhibit limited mobility and remain in the upper layer; some will leach locally into ground water and/ or surface water ecosystems when soaked by rain or melt ice.

Environmental processes may also be important in changing solubilities.

Even though many metals show few toxic effects at physiological pHs, transformation may introduce new or magnified effects.

A metal ion is considered infinitely persistent because it cannot degrade further.

The current state of science does not allow for an unambiguous interpretation of various measures of bioaccumulation.

The counter-ion may also create health and environmental concerns once isolated from the metal. Under normal physiological conditions the counter-ion may be essentially insoluble and may not be bioavailable.

Environmental processes may enhance bioavailability.

Ecotoxicity:

Fish LC50 (96h): 43mg/l

SODIUM HYPOCHLORITE:

Very toxic to aquatic organisms.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters. Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For chlorine:

Environmental fate:

Atmospheric chlorine produced as a result of such process as disinfection forms hydrochloric (HCl) or hypochlorous (HOCl) acid in the atmosphere, either through reactions with hydroxy radicals or other trace species such as hydrocarbons. These acids are believed to be removed from the atmosphere primarily through precipitation washout (i.e. wet deposition as chlorine is scrubbed out by rain in the subcloud layer) or dry deposition as gaseous chlorine contacts and reacts with the earth's surface.

Water chlorination, resulting from municipal and industrial wastewater treatment and cooling water disinfection, initially introduces chlorine into the water as chlorine gas, hypochlorite ion (OCl⁻), or its salt. These forms of chlorine are termed free residual chlorines (FRC). Chlorine in aqueous systems volatilises or quickly decays to residual forms such as hypochlorous acid, chloramine and chlorinated organics. Aquatic chemistry is determined by aquatic factors including pH, ammonium ion (which combines with chlorine to produce chloramine) and certain other reducing agents. Inorganic reducing agents in estuarine waters include sulfur, iron and manganese. Other organic compounds in water also contribute to chlorine decay rate. The reactions of chlorine or hypochlorites in water produce a number of by-products many of which have been implicated as genotoxic or tumourigenic.

Chlorine, added to drinking water as chlorine gas (Cl₂) or hypochlorite salts (e.g., NaOCl), effectively inactivates bacteria in 20 minutes at concentrations of 0.03 to 0.06 mg/l at pH range of 7.0 to 8.5 and temperature range of 4 deg.C to 22 deg.C.

Chlorine disinfectants in wastewater react with organic matters, giving rise to organic chlorine compounds such as AOX (halogenated organic compounds adsorbable on activated carbon), which are toxic for aquatic organisms and are persistent environmental contaminants.

Chlorine hydrolyses very rapidly in water (rate constants range from 1.5 x 10⁻⁴ at deg. C to 4.0 x 10⁻⁴ at 25

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 20 of 24
Section 12 - ECOLOGICAL INFORMATION

deg.C; half-life in natural waters, 0.005 seconds. In fresh and wastewaters at pH >6, complete hydrolysis occurs with the formation of hypochlorous acid (HOCl) and chloride ion (Cl⁻). The hypochlorous acid ionizes to hydrogen ion (H⁺) and hypochlorite ion (OCl⁻). At pH values >5, OCl⁻ predominates; at pH values <5, HOCl predominates. Free chlorine (Cl₂, HOCl, and OCl⁻) reacts rapidly with inorganics such as bromide and more slowly with organic material present in natural waters. These reactions yield chloride, oxidised organics, chloroorganics (including trihalomethanes), oxygen, nitrogen, chlorate, bromate and bromoorganics. Chlorines ultimate aqueous fate is chloride.

Vapourisation of molecular chlorine (Cl₂) from water to the atmosphere may be significant at low pH values and high concentrations (e.g., pH 2 and 3500 mg/l chlorine), but is insignificant at neutral pH and low concentrations.

Vegetation acts as an important sink for chlorine air pollution. Plant exposure to elevated levels of chlorine can cause plant injury; however chlorine tends to be rapidly converted to other less toxic forms. Atmospheric: When chlorine, hypochlorous acid or hydrogen chloride mixes in the atmosphere with water vapour, dilute solutions of strong mineral acids are formed that fall to earth as acid rain, snow, and fog, or acidified dry particles.

Chlorine may react with soil components to form chlorides; depending on their water solubility, these chlorides are easily washed out from the soil.

Bioaccumulation/ bioconcentration: There is no potential for the bioaccumulation or bioconcentration of chlorine.

Ecotoxicity:

Fish LC50 (96 h): 0.015-13.5 mg/l

Chlorine has high acute toxicity to aquatic organisms; many toxicity values are less than or equal to 1 mg/l. Twenty-four-hour LC50 values range from 0.076 to 0.16 mg/l for *Daphnia magna* (water flea) and from 0.005 to 0.1 mg/l for *Daphnia pulex* (cladocern); 48-hour LC50 values range from 5.3 to 12.8 mg/l for *Nitocra spinipes* (snail); and 96-hour LC50 values range from 0.13 to 0.29 mg/L for *Oncorhynchus mykiss* (rainbow trout), from 0.1 to 0.18 mg/l for *Salvelinus fontinalis* (brook trout), and from 0.71-0.82 mg/l for *Lepomis cyanellus* (green sunfish).

Papillomas of the oral cavity in fish have been associated with exposure to chlorinated water supplies.

Chlorine is phytotoxic but is also essential to plant growth; crops need around 2 kg or more of chlorine per acre. Acute toxicity to plants is characterized by defoliation with no leaf symptoms and, in higher plant forms, by spotting of the leaves (at 1.5 mg/m³) and marginal and interveinal injury (at 150-300 mg/m³)

Data from experimental studies indicate that injury to animals occurs only in the presence of high concentrations of chlorine, either in drinking water or the ambient atmosphere.

http://www.epa.gov/chemfact/s_chlori.txt

U.S. ENVIRONMENTAL PROTECTION AGENCY August 1994.

In fresh water, the hypochlorites break down rapidly into non-toxic compounds when exposed to sunlight. In seawater, chlorine levels decline rapidly; however, hypobromite (which is acutely toxic to aquatic organisms) is formed. Sodium and calcium hypochlorite are low in toxicity to avian wildlife, but they are highly toxic to freshwater fish and invertebrates.

Hypochlorite is a highly reactive chemical which, during and after its use in household scenarios, undergoes a variety of reactions. The major one is the oxidation of inorganic and organic species.

A minor reaction, which consumes about 1.5% of the chlorine atoms from hypochlorite, is chlorination, which leads to formation of organohalogen by-products that are often measured by the group parameter, AOX.

Hypochlorite itself is rapidly broken down during use, in the sewer, and if any does reach sewage treatment it will further degrade (half-life of around 0.6 minutes). Predictions have indicated that its concentration will fall to below 1.E-32 ug/l by the end of the sewer, partially due to its reaction with ammonia in the sewer which leads to a subsequent increase in chloramine.

The level of chloramine reaching surface water is estimated to be below 5.E-10 ug/l. Both these concentrations are orders of magnitude below the lowest acute EC50s determined for sodium hypochlorite (EC50 to invertebrates = 5 ug/l) and monochloramine (EC50 to invertebrates = 16 ug/l).

The organohalogen by-products formed from the use of hypochlorite are currently receiving much attention. However, the levels of AOX produced are low (for example, 37 ug/l from bleach use compared to a sewage background level of 106 ug/l), and the organohalogens produced from domestic use of hypochlorite are not believed to have an adverse effect on the environment. Available data indicate that no dioxins are produced, and that the identified AOXs are typically small molecules with a low degree of chlorination and for which

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 21 of 24
Section 12 - ECOLOGICAL INFORMATION

ecotoxicological properties are known or can be predicted. Where drinking water is disinfected by chlorination, the levels of organohalogens in sewage effluent arising from bleach use will be comparable with, and sometimes only a fraction of, those arising from the tap-water. After secondary sewage treatment, the levels entering receiving waters will be of the same order of magnitude as background levels typically present in rivers, though the total flux in rivers from natural sources will be much greater.

The majority of the measured AOX is unidentified, but thought to consist of high molecular weight components formed from fats, proteins and humic acids which are too large to bioaccumulate.

In addition, studies on the whole AOX mixture in laundry waste-water indicated that the level of AOX present did not effect growth or reproduction of Ceriodaphnia, and that around 70% is removed in activated sludge.

The material is classified as an ecotoxin* because the Fish LC50 (96 hours) is less than or equal to 0.1 mg/l

* Classification of Substances as Ecotoxic (Dangerous to the Environment)

Appendix 8, Table 1

Compiler's Guide for the Preparation of International Chemical Safety Cards: 1993 Commission of the European Communities.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
sodium hydroxide	LOW		LOW	HIGH
sodium hypochlorite			LOW	

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle where possible
Otherwise ensure that:
- licenced contractors dispose of the product and its container.
- disposal occurs at a licenced facility.

Section 14 - TRANSPORTATION INFORMATION



DOT:			
Symbols:	None	Hazard class or Division:	8
Identification Numbers:	UN3266	PG:	II
Label Codes:	8	Special provisions:	B2, IB2, T11, TP2, TP27
Packaging: Exceptions:	154	Packaging: Non- bulk:	202
Packaging: Exceptions:	154	Quantity limitations:	1 L
		Passenger aircraft/rail:	

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 22 of 24

Section 14 - TRANSPORTATION INFORMATION

Quantity Limitations: 30 L Vessel stowage: B
Cargo aircraft only: Location:
Vessel stowage: Other: 40, 52
Hazardous materials descriptions and proper shipping names:
Corrosive liquid, basic, inorganic, n.o.s.

Air Transport IATA:

ICAO/IATA Class: 8 ICAO/IATA Subrisk: None
UN/ID Number: 3266 Packing Group: II
Special provisions: A3
Shipping Name: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S.
*(CONTAINS SODIUM HYDROXIDE, SODIUM HYPOCHLORITE)

Maritime Transport IMDG:

IMDG Class: 8 IMDG Subrisk: None
UN Number: 3266 Packing Group: II
EMS Number: F- A, S- B Special provisions: 274 944
Limited Quantities: 1 L Marine Pollutant: Not Determined
Shipping Name: CORROSIVE LIQUID, BASIC, INORGANIC,
N.O.S.(Contains sodium hydroxide, sodium hypochlorite)

Section 15 - REGULATORY INFORMATION

REGULATIONS

Regulations for ingredients

sodium hydroxide (CAS: 1310-73-2) is found on the following regulatory lists;

"Canada - Alberta Occupational Exposure Limits", "Canada - British Columbia Occupational Exposure Limits", "Canada - Northwest Territories Occupational Exposure Limits (English)", "Canada - Nova Scotia Occupational Exposure Limits", "Canada - Ontario Occupational Exposure Limits", "Canada - Prince Edward Island Occupational Exposure Limits", "Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)", "Canada - Saskatchewan Industrial Hazardous Substances", "Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits", "Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances", "Canada Ingredient Disclosure List (SOR/88-64)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (French)", "CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals", "US - Alaska Limits for Air Contaminants", "US - California Air Toxics ""Hot Spots"" List (Assembly Bill 2588) Substances for which emissions must be quantified", "US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List", "US - California OEHA/ARB - Acute Reference Exposure Levels and Target Organs (RELS)", "US - California Permissible Exposure Limits for Chemical Contaminants", "US - California Toxic Air Contaminant List Category II", "US - Connecticut Hazardous Air Pollutants", "US - Hawaii Air Contaminant Limits", "US - Idaho - Limits for Air Contaminants", "US - Massachusetts Oil & Hazardous Material List", "US - Michigan Exposure Limits for Air Contaminants", "US - Minnesota Hazardous Substance List", "US - Minnesota Permissible Exposure Limits (PELs)", "US - New Jersey Right to Know Hazardous Substances", "US - Oregon Permissible Exposure Limits (Z1)", "US - Pennsylvania - Hazardous Substance List", "US - Rhode Island Hazardous Substance List", "US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US - Washington Permissible exposure limits of air contaminants", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US ACGIH Threshold Limit Values (TLV)", "US CWA (Clean Water Act) - List of Hazardous Substances", "US CWA (Clean Water Act) - Reportable Quantities of Designated Hazardous Substances", "US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US EPA High Production Volume Chemicals Additional List", "US Food Additive Database", "US List of Lists - Consolidated List of Chemicals Subject to the Emergency Planning and Community Right-to-Know Act (EPCRA) and Section 112(r) of the Clean Air Act", "US NIOSH Recommended Exposure Limits (RELS)", "US OSHA Permissible Exposure Levels (PELs) - Table Z1", "US Postal Service (USPS) Hazardous Materials Table: Postal Service Mailability Guide", "US Toxic Substances Control Act (TSCA) - Inventory"

sodium hypochlorite (CAS: 7681-52-9,10022-70-5) is found on the following regulatory lists;

"Canada - Saskatchewan Industrial Hazardous Substances", "Canada Ingredient Disclosure List (SOR/88-64)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (French)", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "International Council of Chemical Associations (ICCA) - High Production Volume List", "OECD Representative List of High Production Volume (HPV) Chemicals", "US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List", "US - Massachusetts Oil & Hazardous Material List", "US - Minnesota Hazardous Substance List", "US - New Jersey Right to Know Hazardous Substances", "US - Pennsylvania - Hazardous Substance List", "US AIHA Workplace Environmental Exposure Levels (WEELs)", "US CWA (Clean Water Act) - List of Hazardous Substances", "US CWA (Clean Water Act) - Reportable Quantities of Designated Hazardous Substances", "US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US EPA Master Testing List - Index I Chemicals Listed", "US FDA Indirect Food Additives: Adhesives and Components of Coatings - Substances for Use Only as Components of Adhesives - Adhesives", "US Food Additive Database", "US List of Lists - Consolidated List of Chemicals Subject to the

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 23 of 24
Section 15 - REGULATORY INFORMATION

Emergency Planning and Community Right-to-Know Act (EPCRA) and Section 112(r) of the Clean Air Act", "US Postal Service (USPS) Hazardous Materials Table: Postal Service Mailability Guide", "US Toxic Substances Control Act (TSCA) - Inventory"

No data for Liquid Ammonia Test Solution #2 (CW: 4650-9)

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
sodium hypochlorite	7681- 52- 9, 10022- 70- 5

EXPOSURE STANDARD FOR MIXTURES

"Worst Case" computer-aided prediction of vapour components/concentrations:

Composite Exposure Standard for Mixture (TWA) (mg/m³): 1.5 mg/m³

If the breathing zone concentration of ANY of the components listed below is exceeded, "Worst Case" considerations deem the individual to be overexposed.

Component Breathing Zone ppm Breathing Zone mg/m³ Mixture Conc: (%)

Component	Breathing zone (ppm)	Breathing zone (mg/m ³)	Mixture Conc (%)
sodium hypochlorite	0.50	1.5000	1.0
sodium hypochlorite	0.00	0.0000	0.0

CONTACT

Mars Fishcare

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following U.S. Regulations and Standards:

OSHA Standards - 29 CFR:

1910.132 - Personal Protective Equipment - General requirements

1910.133 - Eye and face protection

1910.134 - Respiratory Protection

1910.136 - Occupational foot protection

1910.138 - Hand Protection

Eye and face protection - ANSI Z87.1

Foot protection - ANSI Z41

Respirators must be NIOSH approved.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

continued...

LIQUID AMMONIA TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-9
Version No:4
CD 2010/1 Page 24 of 24
Section 16 - OTHER INFORMATION

Issue Date: Dec-23-2009
Print Date: May-20-2010

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-16
Version No:6
CD 2010/1 Page 1 of 17

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

OTHER NAMES

"Solution ID# 3317"

PRODUCT USE


Nitrate test solution for products 26, 34 and 401M.

SUPPLIER

Company: Mars Fishcare Inc
Address:
50 East Hamilton Street
Chalfont
PA, 18914
USA
Telephone: +1 215 822 8181
Fax: +1 215 822 1906

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS



GHS Classification

Eye Irritation Category 2A
Skin Corrosion/Irritation Category 3



EMERGENCY OVERVIEW

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-16
Version No:6
CD 2010/1 Page 2 of 17
Section 2 - HAZARDS IDENTIFICATION

HAZARD

WARNING

Determined by Chemwatch using GHS criteria:

H316 H319

Causes mild skin irritation

Causes serious eye irritation

PRECAUTIONARY STATEMENTS

Prevention

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/attention.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
polyethylene glycol	25322-68-3	<95
hydrochloric acid	7647-01-0	0.97

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with eyes:

- Wash out immediately with water.
- If irritation continues, seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin or hair contact occurs:

- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

Treat symptomatically.

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-16
Version No:6
CD 2010/1 Page 3 of 17

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE/EXPLOSION HAZARD

- Combustible.
 - Slight fire hazard when exposed to heat or flame.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
 - On combustion, may emit toxic fumes of carbon monoxide (CO).
 - May emit acrid smoke.
 - Mists containing combustible materials may be explosive.
- Combustion products include: carbon dioxide (CO₂), hydrogen chloride, other pyrolysis products typical of burning organic material, phosgene.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

PERSONAL PROTECTION

Glasses:
Safety Glasses.

Gloves:
When handling larger quantities:

Respirator:
Type B- P Filter of sufficient capacity

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

ACUTE EXPOSURE GUIDELINE LEVELS (AEGL) (in ppm)

hydrochloric acid

AEGL Type	10 min	30 min	60 min	4 hr	8 hr
AEGL 1	1.8	1.8	1.8	1.8	GALSYN~
AEGL 2	100	43	22	11	GALSYN~
AEGL 3	620	210	100	26	GALSYN~

AEGL 1: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-16
Version No:6
CD 2010/1 Page 4 of 17

Section 6 - ACCIDENTAL RELEASE MEASURES

experience notable discomfort, irritation, or certain asymptomatic nonsensory effects. However, the effects are not disabling and are transient and reversible upon cessation of exposure.

AEGL 2: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience irreversible or other serious, long-lasting adverse health effects or an impaired ability to escape.

AEGL 3: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience life-threatening health effects or death.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- DO NOT USE brass or copper containers / stirrers.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+ + + + X +

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Dec-23-2009
 NC614TDP

CHEMWATCH 4650-16
 Version No:6
 CD 2010/1 Page 5 of 17
 Section 7 - HANDLING AND STORAGE

+: May be stored together
 O: May be stored together with specific preventions
 X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

US OSHA Permissible Exposure Levels (PELs)

Z	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Max excursion ppm	Max excursion mg/m ³	Max excursion duration (mins)	TWA F/CC
Z3	Inert or Nuisance Dust: (d) Respirable fraction		5								
Z3	Inert or Nuisance Dust: (d) Total dust		15								
Z1	Hydrogen chloride					5	7				

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Notes
US - Oregon Permissible Exposure Limits (Z3)	polyethylene glycol (Inert or Nuisance Dust: (d) Total dust)		10					*
US OSHA Permissible Exposure Levels (PELs) - Table Z3	polyethylene glycol (Inert or Nuisance Dust: (d) Respirable fraction)		5					
US OSHA Permissible Exposure Levels (PELs) - Table Z3	polyethylene glycol (Inert or Nuisance Dust: (d) Total dust)		15					
US - Hawaii Air Contaminant Limits	polyethylene glycol (Particulates not other wise regulated - Total dust)		10					
US - Hawaii Air Contaminant Limits	polyethylene glycol (Particulates not other wise regulated - Respirable fraction)		5					

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Dec-23-2009
 NC614TDP

CHEMWATCH 4650-16
 Version No:6
 CD 2010/1 Page 6 of 17

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Notes
US - Oregon Permissible Exposure Limits (Z3)	polyethylene glycol (Inert or Nuisance Dust: (d) Respirable fraction)		5					*
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	polyethylene glycol (Particulates not otherwise regulated Respirable fraction)		5					
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	polyethylene glycol (Particulates not otherwise regulated (PNOR)(f)-Respirable fraction)		5					
US - Michigan Exposure Limits for Air Contaminants	polyethylene glycol (Particulates not otherwise regulated, Respirable dust)		5					
Canada - British Columbia Occupational Exposure Limits	hydrochloric acid (Hydrogen chloride Revised 2003)					2		
Canada - Ontario Occupational Exposure Limits	hydrochloric acid (Hydrogen chloride)					2		
US - Minnesota Permissible Exposure Limits (PELs)	hydrochloric acid (Hydrogen chloride)					5	7	
US ACGIH Threshold Limit Values (TLV)	hydrochloric acid (Hydrogen chloride)					2		TLV Basis: upper respiratory tract irritation
US NIOSH Recommended Exposure Limits (RELs)	hydrochloric acid (Hydrogen chloride)					5	7	

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Dec-23-2009
 NC614TDP

CHEMWATCH 4650-16
 Version No:6
 CD 2010/1 Page 7 of 17

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Notes
Canada - Alberta Occupational Exposure Limits	hydrochloric acid (Hydrogen chloride)					2	3	
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	hydrochloric acid (Hydrogen chloride)					5	7	
US - Vermont Permissible Exposure Limits Table Z- 1- A Transitional Limits for Air Contaminants	hydrochloric acid (Hydrogen chloride)	(C)5	(C)7					
US - Vermont Permissible Exposure Limits Table Z- 1- A Final Rule Limits for Air Contaminants	hydrochloric acid (Hydrogen chloride)					5	7	
US - California Permissible Exposure Limits for Chemical Contaminants	hydrochloric acid (Hydrogen chloride; muriatic acid)					5	7	
US - Idaho - Limits for Air Contaminants	hydrochloric acid (Hydrogen chloride)					5	7	
US - Hawaii Air Contaminant Limits	hydrochloric acid (Hydrogen chloride)					5	7	
US - Alaska Limits for Air Contaminants	hydrochloric acid (Hydrogen chloride)					5	7	
US - Michigan Exposure Limits for Air Contaminants	hydrochloric acid (Hydrogen chloride)					5	7	
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	hydrochloric acid (Hydrogen chloride)	5	7	-	-			

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Dec-23-2009
 NC614TDP

CHEMWATCH 4650-16
 Version No:6
 CD 2010/1 Page 8 of 17

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Notes
US - Washington Permissible exposure limits of air contaminants	hydrochloric acid (Hydrogen chloride)					5.0		
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	hydrochloric acid (Hydrogen chloride)					2		
US - Oregon Permissible Exposure Limits (Z1)	hydrochloric acid (Hydrogen chloride)					5	7	
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	hydrochloric acid (Hydrogen chloride)					5	7	
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	hydrochloric acid (Hydrogen chloride)					5	7, 5	
US OSHA Permissible Exposure Levels (PELs) - Table Z1	hydrochloric acid (Hydrogen chloride)					5	7	
Canada - Northwest Territories Occupational Exposure Limits (English)	hydrochloric acid (Hydrogen chloride)					5	7.5	
Canada - Nova Scotia Occupational Exposure Limits	hydrochloric acid (Hydrogen chloride)					2		TLV Basis: upper respiratory tract irritation

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Dec-23-2009
 NC614TDP

CHEMWATCH 4650-16
 Version No:6
 CD 2010/1 Page 9 of 17

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Notes
Canada - Prince Edward Island Occupational Exposure Limits	hydrochloric acid (Hydrogen chloride)					2		TLV Basis: upper respiratory tract irritation

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
hydrochloric acid		50

MATERIAL DATA

POLYETHYLENE GLYCOL:

Not available. Refer to individual constituents.

HYDROCHLORIC ACID:

For powdered forms:

The polyethylene glycols are extremely low in oral toxicity, are not significantly irritating to the eyes or skin, and are not absorbed through the skin in toxic amounts. vapour pressures are extremely low and inhalation exposure is limited to mists. Based on experimental data and human experience, these substances do not present significant hazards to health in the workplace.

PERSONAL PROTECTION



EYE

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-16
Version No:6
CD 2010/1 Page 10 of 17

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

HANDS/FEET

Wear general protective gloves, eg. light weight rubber gloves. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: such as:

- frequency and duration of contact,
- chemical resistance of glove material,
- glove thickness and
- dexterity

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended.
- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended.
- Contaminated gloves should be replaced.

Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

OTHER

No special equipment needed when handling small quantities.

OTHERWISE:

- Overalls.
- Barrier cream.
- Eyewash unit.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	B- AUS P	-
1000	50	-	B- AUS P
5000	50	Airline *	-
5000	100	-	B- 2 P
10000	100	-	B- 3 P
	100+		Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-16
Version No:6
CD 2010/1 Page 11 of 17

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank (in still air)	Air Speed: 0.25- 0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only
- 3: Intermittent, low production.
- 4: Large hood or large air mass in motion

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use
- 4: Small hood - local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Blue-green solution with no odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.
Mixes with water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°F)	Not Available	Viscosity	Not Available
Boiling Range (°F)	Not Available	Solubility in water (g/L)	Miscible
Flash Point (°F)	Not Applicable	pH (1% solution)	Not Available

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-16
Version No:6
CD 2010/1 Page 12 of 17

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Decomposition Temp (°F)	Not Available	pH (as supplied)	Not Available
Autoignition Temp (°F)	Not Applicable	Vapour Pressure (mmHG)	Not Available
Upper Explosive Limit (%)	Not Applicable	Specific Gravity (water=1)	1.128
Lower Explosive Limit (%)	Not Applicable	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available


Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
 - Product is considered stable.
 - Hazardous polymerisation will not occur.
- For incompatible materials - refer to Section 7 - Handling and Storage.*

Section 11 - TOXICOLOGICAL INFORMATION

CHEMWATCH HAZARD RATINGS



POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (eg. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

SKIN

The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-16
Version No:6
CD 2010/1 Page 13 of 17

Section 11 - TOXICOLOGICAL INFORMATION

INHALED

The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

Not normally a hazard due to non-volatile nature of product.

Inhalation hazard is increased at higher temperatures.

CHRONIC HEALTH EFFECTS

Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

TOXICITY AND IRRITATION

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

POLYETHYLENE GLYCOL:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 33750 mg/kg

for molecular weights (200-8000) *

Oral (rat) LD50: 31000->50000 mg/kg

Oral (mice) LD50: 38000->50000 mg/kg

Oral (g.pig) LD50: 17000->50000 mg/kg

Oral (rabbit) LD50: 14000->50000 mg/kg

Intraperitoneal (mice) LD50: 3100-12900 mg/kg

IRRITATION

Skin (rabbit): 500mg/24h - mild.

Eye (rabbit): 500mg/24h - mild.

* AIHA WEEL Guides

HYDROCHLORIC ACID:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Unreported (man) LDLo: 81 mg/kg

Inhalation (human) LCLo: 1300 ppm/30 min

Inhalation (human) LCLo: 3000 ppm/5 min

Inhalation (rat) LC50: 3124 ppm/1h

Oral (rat) LD50: 900 mg/kg

IRRITATION

Eye (rabbit): 5mg/30s - Mild

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-16
Version No:6
CD 2010/1 Page 14 of 17
Section 11 - TOXICOLOGICAL INFORMATION

exposure to irritants may produce conjunctivitis.
The substance is classified by IARC as Group 3:
NOT classifiable as to its carcinogenicity to humans.
Evidence of carcinogenicity may be inadequate or limited in animal testing.

CARCINOGEN

Hydrochloric acid	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3
Hydrogen chloride	US ACGIH Threshold Limit Values (TLV) - Carcinogens	Carcinogen Category	A4

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

POLYETHYLENE GLYCOL:
BOD 5 if unstated: 0-0.02,1%
COD: 1.62-1.74,98%
Toxicity Fish: TLm(96)>10000mg/L

HYDROCHLORIC ACID:
Hazardous Air Pollutant: Yes
Fish LC50 (96hr.) (mg/l): 0.282

Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5.

Although inorganic chloride ions are not normally considered toxic they can exist in effluents at acutely toxic levels (chloride >3000 mg/l). the resulting salinity can exceed the tolerances of most freshwater organisms.

Inorganic chlorine eventually finds its way into the aqueous compartment and as such is bioavailable. Incidental exposure to inorganic chloride may occur in occupational settings where chemicals management policies are improperly applied. The toxicity of chloride salts depends on the counter-ion (cation) present; that of chloride itself is unknown. Chloride toxicity has not been observed in humans except in the special case of impaired sodium chloride metabolism, e.g. in congestive heart failure. Healthy individuals can tolerate the intake of large quantities of chloride provided that there is a concomitant intake of fresh water.

Although excessive intake of drinking-water containing sodium chloride at concentrations above 2.5 g/litre has been reported to produce hypertension, this effect is believed to be related to the sodium ion concentration.

Chloride concentrations in excess of about 250 mg/litre can give rise to detectable taste in water, but the threshold depends upon the associated cations. Consumers can, however, become accustomed to concentrations in excess of 250 mg/litre. No health-based guideline value is proposed for chloride in drinking-water.

In humans, 88% of chloride is extracellular and contributes to the osmotic activity of body fluids. The electrolyte balance in the body is maintained by adjusting total dietary intake and by excretion via the kidneys and gastrointestinal tract. Chloride is almost completely absorbed in normal individuals, mostly from

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-16
Version No:6
CD 2010/1 Page 15 of 17

Section 12 - ECOLOGICAL INFORMATION

the proximal half of the small intestine. Normal fluid loss amounts to about 1.5-2 liters/day, together with about 4 g of chloride per day. Most (90 - 95%) is excreted in the urine, with minor amounts in faeces (4- %) and sweat (2%).

Chloride increases the electrical conductivity of water and thus increases its corrosivity. In metal pipes, chloride reacts with metal ions to form soluble salts thus increasing levels of metals in drinking-water. In lead pipes, a protective oxide layer is built up, but chloride enhances galvanic corrosion. It can also increase the rate of pitting corrosion of metal pipes.

Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

Ecotoxicity

Fish LC100 (24 h): trout 10 mg/l

TLm (96 h): mosquito fish 282 ppm (fresh water)

LC50: goldfish 178 mg/l

Shrimp LC50 (48 h): 100 - 330 ppm (salt water)

Starfish LC50 (48 h): 100 - 330 mg/l

Cockle LC50 (48 h): 330 - 1000 mg/l

[Hach]

Hydrogen chloride in water dissociates almost completely, releasing hydrogen and chloride ions; the hydrogen ions are captured by water to produce hydronium ions.

Hydrochloric acid infiltrates soil, the rate dependent on moisture content. During soil transport, hydrochloric acid dissolves soil components.

Drinking water standard:

chloride: 400 mg/l (UK max.)

250 mg/l (WHO guideline)

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
polyethylene glycol	LOW		LOW	HIGH
hydrochloric acid	LOW		LOW	HIGH

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle where possible
Otherwise ensure that:
- licenced contractors dispose of the product and its container.
- disposal occurs at a licenced facility.

Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

Regulations for ingredients

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-16
Version No:6
CD 2010/1 Page 16 of 17
Section 15 - REGULATORY INFORMATION

polyethylene glycol (CAS: 25322-68-3) is found on the following regulatory lists;

"GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "US - Minnesota Hazardous Substance List", "US Cosmetic Ingredient Review (CIR) Cosmetic ingredients found safe, with qualifications", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US DOT Coast Guard Bulk Hazardous Materials - List of Flammable and Combustible Bulk Liquid Cargoes", "US EPA High Production Volume Program Chemical List", "US FDA Indirect Food Additives: Adhesives and Components of Coatings - Substances for Use Only as Components of Adhesives - Adhesives", "US Food Additive Database", "US Inventory of Effective Food Contact Substance Notifications", "US Toxic Substances Control Act (TSCA) - Inventory"

hydrochloric acid (CAS: 7647-01-0) is found on the following regulatory lists;

"Canada - Alberta Ambient Air Quality Objectives", "Canada - Alberta Occupational Exposure Limits", "Canada - British Columbia Occupational Exposure Limits", "Canada - Northwest Territories Occupational Exposure Limits (English)", "Canada - Nova Scotia Occupational Exposure Limits", "Canada - Ontario Occupational Exposure Limits", "Canada - Prince Edward Island Occupational Exposure Limits", "Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)", "Canada - Saskatchewan Industrial Hazardous Substances", "Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits", "Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances", "Canada Controlled Drugs and Substances Act Schedule VI", "Canada Domestic Substances List (DSL)", "Canada Ingredient Disclosure List (SOR/88-64)", "Canada National Pollutant Release Inventory (NPRI)", "Canada Prohibited Toxic Substances, Schedule 2, Concentration Limits (English)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (French)", "CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Maritime Dangerous Goods Requirements (IMDG Code) - Goods Forbidden for Transport", "OECD Representative List of High Production Volume (HPV) Chemicals", "United Nations Convention Against Illicit Traffic in Narcotic Drugs and Psychotropic Substances - Table II", "United Nations List of Precursors and Chemicals Frequently used in the Illicit Manufacture of Narcotic Drugs and Psychotropic Substances Under International Control - Table II", "US - Alaska Limits for Air Contaminants", "US - California Air Toxics ""Hot Spots"" List (Assembly Bill 2588) Substances for which emissions must be quantified", "US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List", "US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELS)", "US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELS)", "US - California Permissible Exposure Limits for Chemical Contaminants", "US - California Toxic Air Contaminant List Category II", "US - Connecticut Hazardous Air Pollutants", "US - Hawaii Air Contaminant Limits", "US - Idaho - Limits for Air Contaminants", "US - Massachusetts Oil & Hazardous Material List", "US - Michigan Exposure Limits for Air Contaminants", "US - Minnesota Hazardous Substance List", "US - Minnesota Permissible Exposure Limits (PELs)", "US - New Jersey Right to Know Hazardous Substances", "US - Oregon Hazardous Materials", "US - Oregon Permissible Exposure Limits (Z1)", "US - Pennsylvania - Hazardous Substance List", "US - Rhode Island Hazardous Substance List", "US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US - Washington Permissible exposure limits of air contaminants", "US - Wyoming List of Highly Hazardous Chemicals, Toxics and Reactives", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US ACGIH Threshold Limit Values (TLV)", "US ACGIH Threshold Limit Values (TLV) - Carcinogens", "US Clean Air Act - Hazardous Air Pollutants", "US CWA (Clean Water Act) - List of Hazardous Substances", "US CWA (Clean Water Act) - Reportable Quantities of Designated Hazardous Substances", "US Department of Homeland Security Chemical Facility Anti-Terrorism Standards - Chemicals of Interest", "US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US Drug Enforcement Administration (DEA) List I and II Regulated Chemicals", "US EPA Acute Exposure Guideline Levels (AEGLS) - Final", "US EPA High Production Volume Chemicals Additional List", "US EPA Master Testing List - Index I Chemicals Listed", "US EPCRA Section 313 Chemical List", "US Food Additive Database", "US List of Lists - Consolidated List of Chemicals Subject to the Emergency Planning and Community Right-to-Know Act (EPCRA) and Section 112(r) of the Clean Air Act", "US NFPA 45 Fire Protection for Laboratories Using Chemicals - Flammability Characteristics of Common Compressed and Liquefied Gases", "US NIOSH Recommended Exposure Limits (RELs)", "US OSHA List of Highly Hazardous Chemicals, Toxics and Reactives", "US OSHA Permissible Exposure Levels (PELs) - Table Z1", "US Postal Service (USPS) Hazardous Materials Table: Postal Service Mailability Guide", "US SARA Section 302 Extremely Hazardous Substances", "US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants", "US Toxic Substances Control Act (TSCA) - Inventory"

No data for Freshwater/Saltwater Nitrite Test Solution (CW: 4650-16)

Section 16 - OTHER INFORMATION

CONTACT

Mars Fishcare

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following U.S. Regulations and Standards:

OSHA Standards - 29 CFR:

1910.132 - Personal Protective Equipment - General requirements

continued...

FRESHWATER/SALTWATER NITRITE TEST SOLUTION

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-16
Version No:6
CD 2010/1 Page 17 of 17
Section 16 - OTHER INFORMATION

1910.133 - Eye and face protection
1910.134 - Respiratory Protection
1910.136 - Occupational foot protection
1910.138 - Hand Protection
Eye and face protection - ANSI Z87.1
Foot protection - ANSI Z41
Respirators must be NIOSH approved.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Dec-23-2009
Print Date: May-20-2010

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 1 of 18

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

LIQUID NITRATE TEST SOLUTION #1

OTHER NAMES

"Solution ID# 3306"

PROPER SHIPPING NAME

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.(contains hydrochloric acid)

PRODUCT USE


Nitrate test solution for product LR1800, 34 and 401M.

SUPPLIER

Company: Mars Fishcare Inc
Address:
50 East Hamilton Street
Chalfont
PA, 18914
USA
Telephone: +1 215 822 8181
Fax: +1 215 822 1906

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS



GHS Classification

Acute Toxicity (Inhalation) Category 4
Eye Irritation Category 2A
Metal Corrosion Category 1
Respiratory Irritation Category 3
Serious Eye Damage Category 1
Skin Corrosion/Irritation Category 2

continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 2 of 18
Section 2 - HAZARDS IDENTIFICATION



EMERGENCY OVERVIEW

HAZARD

DANGER

Determined by Chemwatch using GHS criteria:

H335 H332 H315 H290 H315 H318 H319

May cause respiratory irritation

Harmful if inhaled

Causes skin irritation

May be corrosive to metals

Causes skin irritation

Causes serious eye damage

Causes serious eye irritation

PRECAUTIONARY STATEMENTS

Prevention

Keep only in original container.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Call a POISON CENTER or doctor/physician if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Absorb spillage to prevent material damage.

Storage

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Store in corrosive resistant container or with a resistant inner liner.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
hydrochloric acid	7647-01-0	14 ap.
other ingredients, proprietary		N/S

continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 3 of 18

Section 4 - FIRST AID MEASURES

SWALLOWED

- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Transport to hospital or doctor without delay.

EYE

If this product comes in contact with the eyes:

- Immediately hold eyelids apart and flush the eye continuously with running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
- Transport to hospital or doctor without delay.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

If skin or hair contact occurs:

- Immediately flush body and clothes with large amounts of water, using safety shower if available.
- Quickly remove all contaminated clothing, including footwear.
- Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.
- Transport to hospital, or doctor.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor, without delay.

NOTES TO PHYSICIAN

For acute or short term repeated exposures to strong acids:

- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.

INGESTION:

- Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.

continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 4 of 18
Section 4 - FIRST AID MEASURES

-
- Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
 - Charcoal has no place in acid management.
 - Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

- Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.
- Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjunctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- Steroid eye drops should only be administered with the approval of a consulting ophthalmologist). [Ellenhorn and Barceloux: Medical Toxicology].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE/EXPLOSION HAZARD

- Non combustible.
 - Not considered to be a significant fire risk.
 - Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
 - May emit corrosive, poisonous fumes. May emit acrid smoke.
- Decomposition may produce toxic fumes of: hydrogen chloride.

FIRE INCOMPATIBILITY

None known.

Personal Protective Equipment

Gas tight chemical resistant suit.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 5 of 18
Section 6 - ACCIDENTAL RELEASE MEASURES

ACUTE EXPOSURE GUIDELINE LEVELS (AEGLE) (in ppm)

hydrochloric acid

AEGLE Type	10 min	30 min	60 min	4 hr	8 hr
AEGLE 1	1.8	1.8	1.8	1.8	GALSYN~
AEGLE 2	100	43	22	11	GALSYN~
AEGLE 3	620	210	100	26	GALSYN~

AEGLE 1: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience notable discomfort, irritation, or certain asymptomatic nonsensory effects. However, the effects are not disabling and are transient and reversible upon cessation of exposure.

AEGLE 2: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience irreversible or other serious, long-lasting adverse health effects or an impaired ability to escape.

AEGLE 3: The airborne concentration of a substance above which it is predicted that the general population, including susceptible individuals, could experience life-threatening health effects or death.

EMERGENCY RESPONSE PLANNING GUIDELINES (ERPG)

The maximum airborne concentration below which it is believed that nearly all individuals could be exposed for up to one hour WITHOUT experiencing or developing

life-threatening health effects is:

hydrochloric acid 150ppm

irreversible or other serious effects or symptoms which could impair an individual's ability to take protective action is:

hydrochloric acid 20ppm

other than mild, transient adverse effects without perceiving a clearly defined odour is:

hydrochloric acid 3ppm

American Industrial Hygiene Association (AIHA)

Ingredients considered according to the following cutoffs

Very Toxic (T+)	>= 0.1%	Toxic (T)	>= 3.0%
R50	>= 0.25%	Corrosive (C)	>= 5.0%
R51	>= 2.5%		
else	>= 10%		

where percentage is percentage of ingredient found in the mixture

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.

continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Nov-19-2009
 NC614TDP

CHEMWATCH 4650-15
 Version No:5
 CD 2010/1 Page 6 of 18
Section 7 - HANDLING AND STORAGE

- **WARNING:** To avoid violent reaction, ALWAYS add material to water and NEVER water to material.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately. Launder contaminated clothing before re-use.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
- DO NOT allow clothing wet with material to stay in contact with skin.

SUITABLE CONTAINER

- DO NOT use aluminium or galvanised containers.
- Check regularly for spills and leaks.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



- +: *May be stored together*
 O: *May be stored together with specific preventions*
 X: *Must not be stored together*

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

US OSHA Permissible Exposure Levels (PELs)

Z	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Max excursion ppm	Max excursion mg/m ³	Max excursion duration (mins)	TWA F/CC
Z1	Hydrogen chloride					5	7				

continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 7 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

US OSHA Permissible Exposure Levels (PELs)

Z	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Max excursion ppm	Max excursion mg/m ³	Max excursion duration (mins)	TWA F/CC
Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Notes			
Canada - British Columbia Occupational Exposure Limits	hydrochloric acid (Hydrogen chloride Revised 2003)					2					
Canada - Ontario Occupational Exposure Limits	hydrochloric acid (Hydrogen chloride)					2					
US - Minnesota Permissible Exposure Limits (PELs)	hydrochloric acid (Hydrogen chloride)					5	7				
US ACGIH Threshold Limit Values (TLV)	hydrochloric acid (Hydrogen chloride)					2					TLV Basis: upper respiratory tract irritation
US NIOSH Recommended Exposure Limits (RELs)	hydrochloric acid (Hydrogen chloride)					5	7				
Canada - Alberta Occupational Exposure Limits	hydrochloric acid (Hydrogen chloride)					2	3				
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	hydrochloric acid (Hydrogen chloride)					5	7				
US - Vermont Permissible Exposure Limits Table Z- 1- A Transitional Limits for Air Contaminants	hydrochloric acid (Hydrogen chloride)		(C)5		(C)7						
US - Vermont Permissible Exposure Limits Table Z- 1- A Final Rule Limits for Air Contaminants	hydrochloric acid (Hydrogen chloride)					5	7				

continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Nov-19-2009
 NC614TDP

CHEMWATCH 4650-15
 Version No:5
 CD 2010/1 Page 8 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Notes
US - California Permissible Exposure Limits for Chemical Contaminants	hydrochloric acid (Hydrogen chloride; muriatic acid)					5	7	
US - Idaho - Limits for Air Contaminants	hydrochloric acid (Hydrogen chloride)					5	7	
US - Hawaii Air Contaminant Limits	hydrochloric acid (Hydrogen chloride)					5	7	
US - Alaska Limits for Air Contaminants	hydrochloric acid (Hydrogen chloride)					5	7	
US - Michigan Exposure Limits for Air Contaminants	hydrochloric acid (Hydrogen chloride)					5	7	
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	hydrochloric acid (Hydrogen chloride)	5	7	-	-			
US - Washington Permissible exposure limits of air contaminants	hydrochloric acid (Hydrogen chloride)					5.0		
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	hydrochloric acid (Hydrogen chloride)					2		
US - Oregon Permissible Exposure Limits (Z1)	hydrochloric acid (Hydrogen chloride)					5	7	
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	hydrochloric acid (Hydrogen chloride)					5	7	

continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 9 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Notes
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	hydrochloric acid (Hydrogen chloride)					5	7, 5	
US OSHA Permissible Exposure Levels (PELs) - Table Z1	hydrochloric acid (Hydrogen chloride)					5	7	
Canada - Northwest Territories Occupational Exposure Limits (English)	hydrochloric acid (Hydrogen chloride)					5	7.5	
Canada - Nova Scotia Occupational Exposure Limits	hydrochloric acid (Hydrogen chloride)					2		TLV Basis: upper respiratory tract irritation
Canada - Prince Edward Island Occupational Exposure Limits	hydrochloric acid (Hydrogen chloride)					2		TLV Basis: upper respiratory tract irritation

EMERGENCY EXPOSURE LIMITS

Material	Revised IDLH Value (mg/m ³)	Revised IDLH Value (ppm)
hydrochloric acid		50

MATERIAL DATA

HYDROCHLORIC ACID:
 Not available. Refer to individual constituents.

PERSONAL PROTECTION



continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 10 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EYE

- Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure
- Chemical goggles whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted
- Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.
- Alternatively a gas mask may replace splash goggles and face shields.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

- Elbow length PVC gloves.
- When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Ensure there is ready access to a safety shower.

RESPIRATOR

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	B- AUS P	-
1000	50	-	B- AUS P
5000	50	Airline *	-
5000	100	-	B- 2 P
10000	100	-	B- 3 P
	100+		Airline**

* - Continuous Flow ** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 11 of 18

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to obtain adequate protection. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank (in still air).	Air Speed: 0.25- 0.5 m/s (50- 100 f/min.)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 12 of 18

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Yellow-orange highly acidic liquid with no odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.
Mixes with water.
Corrosive.
Acid.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°F)	Not Available	Viscosity	Not Available
Boiling Range (°F)	Not Available	Solubility in water (g/L)	Miscible
Flash Point (°F)	Not Applicable	pH (1% solution)	Not Available
Decomposition Temp (°F)	Not Available	pH (as supplied)	<1
Autoignition Temp (°F)	Not Applicable	Vapour Pressure (mmHG)	Not Available
Upper Explosive Limit (%)	Not Applicable	Specific Gravity (water=1)	1.155
Lower Explosive Limit (%)	Not Applicable	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available


Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Contact with alkaline material liberates heat.
 - Presence of incompatible materials.
 - Product is considered stable.
 - Hazardous polymerisation will not occur.
- For incompatible materials - refer to Section 7 - Handling and Storage.*

Section 11 - TOXICOLOGICAL INFORMATION

CHEMWATCH HAZARD RATINGS



POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 13 of 18
Section 11 - TOXICOLOGICAL INFORMATION

SWALLOWED

Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident. Swelling of the epiglottis may make it difficult to breathe which may result in suffocation. More severe exposure may result in vomiting blood and thick mucus, shock, abnormally low blood pressure, fluctuating pulse, shallow respiration and clammy skin, inflammation of stomach wall, and rupture of oesophageal tissue. Untreated shock may eventually result in kidney failure. Severe cases may result in perforation of the stomach and abdominal cavity with consequent infection, rigidity and fever. There may be severe narrowing of the oesophageal or pyloric sphincters; this may occur immediately or after a delay of weeks to years. There may be coma and convulsions, followed by death due to infection of the abdominal cavity, kidneys or lungs.

EYE

This material can cause eye irritation and damage in some persons.
If applied to the eyes, this material causes severe eye damage.
Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns. Mild burns of the epithelia generally recover rapidly and completely. Severe burns produce long-lasting and possibly irreversible damage. The appearance of the burn may not be apparent for several weeks after the initial contact. The cornea may ultimately become deeply opaque resulting in blindness.

SKIN

This material can cause inflammation of the skin on contact in some persons.
Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue.
Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

If inhaled, this material can irritate the throat and lungs of some persons.
Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.
There is some evidence to suggest that this material can cause, if inhaled once, irreversible damage of organs.
Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness. Swelling of the lungs can occur, either immediately or after a delay; symptoms of this include chest tightness, shortness of breath, frothy phlegm and cyanosis. Lack of oxygen can cause death hours after onset.

CHRONIC HEALTH EFFECTS

Repeated or prolonged exposure to acids may result in the erosion of teeth, swelling and/or ulceration of mouth lining. Irritation of airways to lung, with cough, and inflammation of lung tissue often occurs. Chronic exposure may inflame the skin or conjunctiva.
Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.
There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

HYDROCHLORIC ACID:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

IRRITATION

continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 14 of 18

Section 11 - TOXICOLOGICAL INFORMATION

Unreported (man) LDLo: 81 mg/kg
Inhalation (human) LCLo: 1300 ppm/30 min
Inhalation (human) LCLo: 3000 ppm/5 min
Inhalation (rat) LC50: 3124 ppm/1h
Oral (rat) LD50: 900 mg/kg

Eye (rabbit): 5mg/30s - Mild

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

CARCINOGEN

Hydrochloric acid	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3
Hydrogen chloride	US ACGIH Threshold Limit Values (TLV) - Carcinogens	Carcinogen Category	A4

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

HYDROCHLORIC ACID:

LIQUID NITRATE TEST SOLUTION #1:

DO NOT discharge into sewer or waterways.

Prevent, by any means available, spillage from entering drains or water courses.

LIQUID NITRATE TEST SOLUTION #1:

Marine Pollutant: Not Determined

HYDROCHLORIC ACID:

Hazardous Air Pollutant: Yes
Fish LC50 (96hr.) (mg/l): 0.282

Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test

continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 15 of 18
Section 12 - ECOLOGICAL INFORMATION

species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5.

Although inorganic chloride ions are not normally considered toxic they can exist in effluents at acutely toxic levels (chloride >3000 mg/l). the resulting salinity can exceed the tolerances of most freshwater organisms.

Inorganic chlorine eventually finds its way into the aqueous compartment and as such is bioavailable. Incidental exposure to inorganic chloride may occur in occupational settings where chemicals management policies are improperly applied. The toxicity of chloride salts depends on the counter-ion (cation) present; that of chloride itself is unknown. Chloride toxicity has not been observed in humans except in the special case of impaired sodium chloride metabolism, e.g. in congestive heart failure. Healthy individuals can tolerate the intake of large quantities of chloride provided that there is a concomitant intake of fresh water.

Although excessive intake of drinking-water containing sodium chloride at concentrations above 2.5 g/litre has been reported to produce hypertension, this effect is believed to be related to the sodium ion concentration.

Chloride concentrations in excess of about 250 mg/litre can give rise to detectable taste in water, but the threshold depends upon the associated cations. Consumers can, however, become accustomed to concentrations in excess of 250 mg/litre. No health-based guideline value is proposed for chloride in drinking-water.

In humans, 88% of chloride is extracellular and contributes to the osmotic activity of body fluids. The electrolyte balance in the body is maintained by adjusting total dietary intake and by excretion via the kidneys and gastrointestinal tract. Chloride is almost completely absorbed in normal individuals, mostly from the proximal half of the small intestine. Normal fluid loss amounts to about 1.5-2 liters/day, together with about 4 g of chloride per day. Most (90 - 95%) is excreted in the urine, with minor amounts in faeces (4- %) and sweat (2%).

Chloride increases the electrical conductivity of water and thus increases its corrosivity. In metal pipes, chloride reacts with metal ions to form soluble salts thus increasing levels of metals in drinking-water. In lead pipes, a protective oxide layer is built up, but chloride enhances galvanic corrosion. It can also increase the rate of pitting corrosion of metal pipes.

Ecotoxicity

Fish LC100 (24 h): trout 10 mg/l

TLm (96 h): mosquito fish 282 ppm (fresh water)

LC50: goldfish 178 mg/l

Shrimp LC50 (48 h): 100 - 330 ppm (salt water)

Starfish LC50 (48 h): 100 - 330 mg/l

Cockle LC50 (48 h): 330 - 1000 mg/l

[Hach]

Hydrogen chloride in water dissociates almost completely, releasing hydrogen and chloride ions; the hydrogen ions are captured by water to produce hydronium ions.

Hydrochloric acid infiltrates soil, the rate dependent on moisture content. During soil transport, hydrochloric acid dissolves soil components.

Drinking water standard:

chloride: 400 mg/l (UK max.)

250 mg/l (WHO guideline)

Ecotoxicity

Ingredient

Persistence:
Water/Soil

Persistence: Air

Bioaccumulation

Mobility

hydrochloric acid

LOW

LOW

HIGH

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 16 of 18

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle where possible
Otherwise ensure that:
- licenced contractors dispose of the product and its container.
- disposal occurs at a licenced facility.

Section 14 - TRANSPORTATION INFORMATION



DOT:

Symbols:	None	Hazard class or Division:	8
Identification Numbers:	UN3264	PG:	III
Label Codes:	8	Special provisions:	IB3, T7, TP1, TP28
Packaging: Exceptions:	154	Packaging: Non- bulk:	203
Packaging: Exceptions:	154	Quantity limitations:	5 L
		Passenger aircraft/rail:	
Quantity Limitations:	60 L	Vessel stowage:	A
Cargo aircraft only:		Location:	
Vessel stowage: Other:	40		

Hazardous materials descriptions and proper shipping names:
Corrosive liquid, acidic, inorganic, n.o.s

Air Transport IATA:

ICAO/IATA Class:	8	ICAO/IATA Subrisk:	None
UN/ID Number:	3264	Packing Group:	III
Special provisions:	A3		

Shipping Name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
*(CONTAINS HYDROCHLORIC ACID)

Maritime Transport IMDG:

IMDG Class:	8	IMDG Subrisk:	None
UN Number:	3264	Packing Group:	III
EMS Number:	F- A, S- B	Special provisions:	223 274 944
Limited Quantities:	5 L	Marine Pollutant:	Not Determined

Shipping Name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.(contains hydrochloric acid)

continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 17 of 18

Section 15 - REGULATORY INFORMATION

REGULATIONS

Regulations for ingredients

hydrochloric acid (CAS: 7647-01-0) is found on the following regulatory lists;

"Canada - Alberta Ambient Air Quality Objectives", "Canada - Alberta Occupational Exposure Limits", "Canada - British Columbia Occupational Exposure Limits", "Canada - Northwest Territories Occupational Exposure Limits (English)", "Canada - Nova Scotia Occupational Exposure Limits", "Canada - Ontario Occupational Exposure Limits", "Canada - Prince Edward Island Occupational Exposure Limits", "Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)", "Canada - Saskatchewan Industrial Hazardous Substances", "Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits", "Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances", "Canada Controlled Drugs and Substances Act Schedule VI", "Canada Domestic Substances List (DSL)", "Canada Ingredient Disclosure List (SOR/88-64)", "Canada National Pollutant Release Inventory (NPRI)", "Canada Prohibited Toxic Substances, Schedule 2, Concentration Limits (English)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (English)", "Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS (French)", "CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Maritime Dangerous Goods Requirements (IMDG Code) - Goods Forbidden for Transport", "OECD Representative List of High Production Volume (HPV) Chemicals", "United Nations Convention Against Illicit Traffic in Narcotic Drugs and Psychotropic Substances - Table II", "United Nations List of Precursors and Chemicals Frequently used in the Illicit Manufacture of Narcotic Drugs and Psychotropic Substances Under International Control - Table II", "US - Alaska Limits for Air Contaminants", "US - California Air Toxics "Hot Spots" List (Assembly Bill 2588) Substances for which emissions must be quantified", "US - California Occupational Safety and Health Regulations (CAL/OSHA) - Hazardous Substances List", "US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)", "US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US - California Permissible Exposure Limits for Chemical Contaminants", "US - California Toxic Air Contaminant List Category II", "US - Connecticut Hazardous Air Pollutants", "US - Hawaii Air Contaminant Limits", "US - Idaho - Limits for Air Contaminants", "US - Massachusetts Oil & Hazardous Material List", "US - Michigan Exposure Limits for Air Contaminants", "US - Minnesota Hazardous Substance List", "US - Minnesota Permissible Exposure Limits (PELs)", "US - New Jersey Right to Know Hazardous Substances", "US - Oregon Hazardous Materials", "US - Oregon Permissible Exposure Limits (Z1)", "US - Pennsylvania - Hazardous Substance List", "US - Rhode Island Hazardous Substance List", "US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US - Washington Permissible exposure limits of air contaminants", "US - Wyoming List of Highly Hazardous Chemicals, Toxics and Reactives", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US ACGIH Threshold Limit Values (TLV)", "US ACGIH Threshold Limit Values (TLV) - Carcinogens", "US Clean Air Act - Hazardous Air Pollutants", "US CWA (Clean Water Act) - List of Hazardous Substances", "US CWA (Clean Water Act) - Reportable Quantities of Designated Hazardous Substances", "US Department of Homeland Security Chemical Facility Anti-Terrorism Standards - Chemicals of Interest", "US Department of Transportation (DOT) List of Hazardous Substances and Reportable Quantities - Hazardous Substances Other Than Radionuclides", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US Drug Enforcement Administration (DEA) List I and II Regulated Chemicals", "US EPA Acute Exposure Guideline Levels (AEGs) - Final", "US EPA High Production Volume Chemicals Additional List", "US EPA Master Testing List - Index I Chemicals Listed", "US EPCRA Section 313 Chemical List", "US Food Additive Database", "US List of Lists - Consolidated List of Chemicals Subject to the Emergency Planning and Community Right-to-Know Act (EPCRA) and Section 112(r) of the Clean Air Act", "US NFPA 45 Fire Protection for Laboratories Using Chemicals - Flammability Characteristics of Common Compressed and Liquefied Gases", "US NIOSH Recommended Exposure Limits (RELs)", "US OSHA List of Highly Hazardous Chemicals, Toxics and Reactives", "US OSHA Permissible Exposure Levels (PELs) - Table Z1", "US Postal Service (USPS) Hazardous Materials Table: Postal Service Mailability Guide", "US SARA Section 302 Extremely Hazardous Substances", "US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants", "US Toxic Substances Control Act (TSCA) - Inventory"

No data for Liquid Nitrate Test Solution #1 (CW: 4650-15)

Section 16 - OTHER INFORMATION

CONTACT

Mars Fishcare

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following U.S. Regulations and Standards:
OSHA Standards - 29 CFR:

continued...

LIQUID NITRATE TEST SOLUTION #1

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Nov-19-2009
NC614TDP

CHEMWATCH 4650-15
Version No:5
CD 2010/1 Page 18 of 18
Section 16 - OTHER INFORMATION

1910.132 - Personal Protective Equipment - General requirements
1910.133 - Eye and face protection
1910.134 - Respiratory Protection
1910.136 - Occupational foot protection
1910.138 - Hand Protection
Eye and face protection - ANSI Z87.1
Foot protection - ANSI Z41
Respirators must be NIOSH approved.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Nov-19-2009
Print Date: May-20-2010

LIQUID NITRATE TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-20
Version No:4
CD 2010/1 Page 1 of 14

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

LIQUID NITRATE TEST SOLUTION #2

OTHER NAMES

"Solution ID# 3307"

PRODUCT USE

Nitrate test solution for product LR1800, 34 and 401M..

SUPPLIER

Company: Mars Fishcare North America, Inc.

Address:


50 E. Hamilton Street

Chalfont, PA 18914

Telephone: 215- 822- 8181

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS



GHS Classification

Eye Irritation Category 2B

Germ Cell Mutagen Category 1B

Reproductive Toxicity Category 1B

Reproductive Toxicity Category 2

Respiratory Irritation Category 3

Skin Corrosion/Irritation Category 3



EMERGENCY OVERVIEW

continued...

LIQUID NITRATE TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-20
Version No:4
CD 2010/1 Page 2 of 14
Section 2 - HAZARDS IDENTIFICATION

HAZARD

DANGER

Determined by Chemwatch using GHS criteria:

H335 H316 H320 H340 H360 H361

May cause respiratory irritation

Causes mild skin irritation

Causes eye irritation

May cause genetic defects

May damage fertility

Suspected of damaging the unborn child

PRECAUTIONARY STATEMENTS

Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Use personal protective equipment as required.

Response

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/ attention.

Call a POISON CENTER or doctor/physician if you feel unwell.

If skin irritation occurs: Get medical advice/ attention.

If eye irritation persists: Get medical advice/attention.

Storage

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
polyethylene glycol	25322-68-3	98
sulfanilamide	63-74-1	<5

Section 4 - FIRST AID MEASURES

SWALLOWED

- Immediately give a glass of water.
- First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

EYE

If this product comes in contact with the eyes:

- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by

continued...

LIQUID NITRATE TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-20
Version No:4
CD 2010/1 Page 3 of 14
Section 4 - FIRST AID MEASURES

- occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
 - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Other measures are usually unnecessary.

NOTES TO PHYSICIAN

Treat symptomatically.

In cases of recent sulfonamide overdose the stomach should be emptied by aspiration and lavage. If kidney function is adequate, a saline purgative, such as sodium sulfate, 30 g in 250 ml water, may be given to promote peristalsis and elimination of sulfonamide in the urine may be assisted by giving alkalies, such as sodium bicarbonate and increasing fluid intake. Severe crystalluria may require ureteric catheterisation and irrigation with warm 2.5% sodium bicarbonate solution. Treatment should be continued until it can be assumed that the sulfonamide has been eliminated. The majority of sulfonamides are metabolised to acetylated derivatives which retain the toxicity of the parent compound and thus may indicate more active removal when adverse effects are very severe. Active measures may include forced diuresis, peritoneal dialysis and charcoal haemoperfusion.

[Martindale: The Extra Pharmacopoeia, 28th Ed.].

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE/EXPLOSION HAZARD

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Combustion products include: carbon dioxide (CO₂), nitrogen oxides (NO_x), sulfur oxides (SO_x), other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

continued...

LIQUID NITRATE TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-20
Version No:4
CD 2010/1 Page 4 of 14
Section 5 - FIRE FIGHTING MEASURES

PERSONAL PROTECTION

Glasses:
Chemical goggles.

Gloves:
PVC chemical resistant type.

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- DO NOT USE brass or copper containers / stirrers.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.
- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
- DO NOT allow clothing wet with material to stay in contact with skin.

SUITABLE CONTAINER

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.

continued...

LIQUID NITRATE TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
 For Domestic Use Only.
 Dec-23-2009
 NC614TDP

CHEMWATCH 4650-20
 Version No:4
 CD 2010/1 Page 5 of 14
 Section 7 - HANDLING AND STORAGE

- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



- +: May be stored together
 O: May be stored together with specific precautions
 X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

US OSHA Permissible Exposure Levels (PELs)

Z	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Max excursion ppm	Max excursion mg/m ³	Max excursion duration (mins)	TWA F/CC
Z3	Inert or Nuisance Dust: (d) Respirable fraction		5								
Z3	Inert or Nuisance Dust: (d) Total dust		15								
Z3	Inert or Nuisance Dust: (d) Respirable fraction		5								
Z3	Inert or Nuisance Dust: (d) Total dust		15								

Source	Material	TWA mg/m ³	Notes
US - Oregon Permissible Exposure Limits (Z3)	polyethylene glycol (Inert or Nuisance Dust: (d) Total dust)	10	*
US OSHA Permissible Exposure Levels (PELs) - Table Z3	polyethylene glycol (Inert or Nuisance Dust: (d) Respirable fraction)	5	
US OSHA Permissible Exposure Levels (PELs) - Table Z3	polyethylene glycol (Inert or Nuisance Dust: (d) Total dust)	15	
US - Hawaii Air Contaminant Limits	polyethylene glycol (Particulates not other wise regulated - Total dust)	10	
US - Hawaii Air Contaminant Limits	polyethylene glycol (Particulates not other wise regulated - Respirable fraction)	5	

continued...

LIQUID NITRATE TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-20
Version No:4
CD 2010/1 Page 6 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA mg/m ³	Notes
US - Oregon Permissible Exposure Limits (Z3)	polyethylene glycol (Inert or Nuisance Dust: (d) Respirable fraction)	5	*
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	polyethylene glycol (Particulates not otherwise regulated Respirable fraction)	5	
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	polyethylene glycol (Particulates not otherwise regulated (PNOR)(f)- Respirable fraction)	5	
US - Michigan Exposure Limits for Air Contaminants	polyethylene glycol (Particulates not otherwise regulated, Respirable dust)	5	
US - Oregon Permissible Exposure Limits (Z3)	sulfanilamide (Inert or Nuisance Dust: (d) Total dust)	10	*
US OSHA Permissible Exposure Levels (PELs) - Table Z3	sulfanilamide (Inert or Nuisance Dust: (d) Respirable fraction)	5	
US OSHA Permissible Exposure Levels (PELs) - Table Z3	sulfanilamide (Inert or Nuisance Dust: (d) Total dust)	15	
US - Hawaii Air Contaminant Limits	sulfanilamide (Particulates not otherwise regulated - Total dust)	10	
US - Hawaii Air Contaminant Limits	sulfanilamide (Particulates not otherwise regulated - Respirable fraction)	5	
US - Oregon Permissible Exposure Limits (Z3)	sulfanilamide (Inert or Nuisance Dust: (d) Respirable fraction)	5	*
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	sulfanilamide (Particulates not otherwise regulated Respirable fraction)	5	
US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants	sulfanilamide (Particulates not otherwise regulated (PNOR)(f)- Respirable fraction)	5	
US - Michigan Exposure Limits for Air Contaminants	sulfanilamide (Particulates not otherwise regulated, Respirable dust)	5	

MATERIAL DATA

LIQUID NITRATE TEST SOLUTION #2:
Not available

POLYETHYLENE GLYCOL:

For powdered forms:

The polyethylene glycols are extremely low in oral toxicity, are not significantly irritating to the eyes or skin, and are not absorbed through the skin in toxic amounts. vapour pressures are extremely low and inhalation exposure is limited to mists. Based on experimental data and human experience, these substances do not present significant hazards to health in the workplace.

continued...

LIQUID NITRATE TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-20
Version No:4
CD 2010/1 Page 7 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

SULFANILAMIDE:

It is the goal of the ACGIH (and other Agencies) to recommend TLVs (or their equivalent) for all substances for which there is evidence of health effects at airborne concentrations encountered in the workplace.

At this time no TLV has been established, even though this material may produce adverse health effects (as evidenced in animal experiments or clinical experience). Airborne concentrations must be maintained as low as is practically possible and occupational exposure must be kept to a minimum.


NOTE: The ACGIH occupational exposure standard for Particles Not Otherwise Specified (P.N.O.S) does NOT apply.

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations. Present day expectations require that nearly every individual should be protected against even minor sensory irritation and exposure standards are established using uncertainty factors or safety factors of 5 to 10 or more. On occasion animal no-observable-effect-levels (NOEL) are used to determine these limits where human results are unavailable. An additional approach, typically used by the TLV committee (USA) in determining respiratory standards for this group of chemicals, has been to assign ceiling values (TLV C) to rapidly acting irritants and to assign short-term exposure limits (TLV STELs) when the weight of evidence from irritation, bioaccumulation and other endpoints combine to warrant such a limit. In contrast the MAK Commission (Germany) uses a five-category system based on intensive odour, local irritation, and elimination half-life. However this system is being replaced to be consistent with the European Union (EU) Scientific Committee for Occupational Exposure Limits (SCOEL); this is more closely allied to that of the USA.

OSHA (USA) concluded that exposure to sensory irritants can:

- cause inflammation
- cause increased susceptibility to other irritants and infectious agents
- lead to permanent injury or dysfunction
- permit greater absorption of hazardous substances and
- acclimate the worker to the irritant warning properties of these substances thus increasing the risk of overexposure.

PERSONAL PROTECTION



EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

continued...

LIQUID NITRATE TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-20
Version No:4
CD 2010/1 Page 8 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

HANDS/FEET

- Wear chemical protective gloves, eg. PVC.
- Wear safety footwear or safety gumboots, eg. Rubber.

OTHER

- Overalls.
- P.V.C. apron.
- Barrier cream.
- Skin cleansing cream.
- Eye wash unit.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required. For further information consult site specific CHEMWATCH data (if available), or your Occupational Health and Safety Advisor.

ENGINEERING CONTROLS

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in special circumstances. If risk of overexposure exists, wear approved respirator. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. Provide adequate ventilation in warehouses and enclosed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank (in still air).	Air Speed: 0.25- 0.5 m/s (50- 100 f/min)
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5- 1 m/s (100- 200 f/min.)
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1- 2.5 m/s (200- 500 f/min.)
grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion)	2.5- 10 m/s (500- 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range

- 1: Room air currents minimal or favourable to capture
- 2: Contaminants of low toxicity or of nuisance value only.
- 3: Intermittent, low production.

Upper end of the range

- 1: Disturbing room air currents
- 2: Contaminants of high toxicity
- 3: High production, heavy use

continued...

LIQUID NITRATE TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-20
Version No:4
CD 2010/1 Page 9 of 14

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

4: Large hood or large air mass in motion

4: Small hood- local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Translucent light gray liquid with no odour; mixes with water.

PHYSICAL PROPERTIES

Liquid.
Mixes with water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°F)	Not Available	Viscosity	Not Available
Boiling Range (°F)	Not Available	Solubility in water (g/L)	Miscible
Flash Point (°F)	Not Applicable	pH (1% solution)	Not Available
Decomposition Temp (°F)	Not Available	pH (as supplied)	Not Available
Autoignition Temp (°F)	Not Applicable	Vapour Pressure (mmHG)	Not Available
Upper Explosive Limit (%)	Not Applicable	Specific Gravity (water=1)	1.127
Lower Explosive Limit (%)	Not Applicable	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION


CHEMWATCH HAZARD RATINGS

continued...

LIQUID NITRATE TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-20
Version No:4
CD 2010/1 Page 10 of 14
Section 11 - TOXICOLOGICAL INFORMATION



POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (eg. liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

Limited evidence or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals. Prolonged eye contact may cause inflammation characterised by a temporary redness of the conjunctiva (similar to windburn).

Eye drops with sulfonamides can cause local irritation, sensations of burning and stinging, blurred vision and loss of depth perception. The conjunctiva and cornea may become inflamed, and the cornea and lens may become clouded.

SKIN

There is some evidence to suggest that the material may cause mild but significant inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Not normally a hazard due to non-volatile nature of product.

CHRONIC HEALTH EFFECTS

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

There is some evidence from animal testing that exposure to this material may result in reduced fertility. Prolonged oral treatment with sulfonamides has caused nausea, vomiting, diarrhoea, abdominal pain, loss of appetite, inflammation of the mouth cavity, impaired folic acid absorption, exacerbation of porphyria, acidosis, liver damage with impaired blood clotting, jaundice and inflammation of the pancreas. Effects on the kidney include blood and crystals in the urine, painful and frequent urination or lack of urine with nitrogen retention. Nervous system symptoms include headache, drowsiness, trouble sleeping, dizziness, ringing in the ears, hearing loss, depression, hallucinations, inco-ordination, paralysis of muscles, numbness in the extremities, spinal cord damage and inflammation, convulsions and unconsciousness. Effects on the blood include a change in blood cell distribution with loss of white blood cells and platelets, and

continued...

LIQUID NITRATE TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-20
Version No:4
CD 2010/1 Page 11 of 14

Section 11 - TOXICOLOGICAL INFORMATION

anaemia, which Africans seem to be more prone to developing than Europeans. Cyanosis can occur owing to complexes being formed by haemoglobin. Eye effects include inflamed cornea and conjunctiva with eyelid swelling and in severe cases, fear of the light. Allergies and cross-sensitivity is common, and can cause itches, wheals and sometimes a severe red rash with blisters that is often fatal. This class of drugs can scar the cornea and conjunctiva, cause swelling around the eyes, painful and inflamed joints, reduced sperm counts, pneumonia, fever, chills, hair loss, inflammation of vessels, lupus, reduced lung function, infertility, hypothyroidism and goitre, and increased urinary output. More seriously, the lungs may become permanently scarred and there may be irreversible damage to the nervous system and muscles. Inflammation of the skin has occurred after the drug is ingested and has travelled through the bloodstream. Skin effects often occur when there has been exposure in conjunction with UV light. Clothed areas are initially less likely to be affected but may be in later stages. Rarely there may be persistence of inflammation on light contact even after the drug has been removed.

TOXICITY AND IRRITATION

Not available. Refer to individual constituents.

POLYETHYLENE GLYCOL:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (rat) LD50: 33750 mg/kg

for molecular weights (200-8000) *

Oral (rat) LD50: 31000->50000 mg/kg

Oral (mice) LD50: 38000->50000 mg/kg

Oral (g.pig) LD50: 17000->50000 mg/kg

Oral (rabbit) LD50: 14000->50000 mg/kg

Intraperitoneal (mice) LD50: 3100-12900 mg/kg

IRRITATION

Skin (rabbit): 500mg/24h - mild.

Eye (rabbit): 500mg/24h - mild.

* AIHA WEEL Guides

SULFANILAMIDE:

unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. No significant acute toxicological data identified in literature search.

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

SULFANILAMIDE:

continued...

LIQUID NITRATE TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-20
Version No:4
CD 2010/1 Page 12 of 14
Section 12 - ECOLOGICAL INFORMATION

LIQUID NITRATE TEST SOLUTION #2:

DO NOT discharge into sewer or waterways.

LIQUID NITRATE TEST SOLUTION #2:

POLYETHYLENE GLYCOL:

BOD 5 if unstated: 0-0.02,1%

COD: 1.62-1.74,98%

Toxicity Fish: TLm(96)>10000mg/L

SULFANILAMIDE:

Toxic to soil organisms.

The sulfonamides are bipolar substances due to their polar functional groups with two pKa-values in the environmentally relevant pH-range. At low pH-values they are cationic due to protonation of the aniline group (pKa1). The isoelectric point is between pH 4 and 5, resulting in neutral species under slightly acidic conditions (pH 3 to 6). At higher pH-values the sulfonamides are anionic due to the deprotonation of the sulfonamide nitrogen group (pKa2). As a consequence of this speciation, the partitioning and the reactivity are pH-dependent which plays an important role for assessing their environmental behavior as well as for their extraction from different matrices for chemical analysis.

Antibiotic sulfonamides, a structurally related group of substances, contain a similar 4-aminobenzene sulfonamide backbone, and are used in agriculture, aquaculture, animal husbandry, and also as human medicines. After animal medication, they are excreted in high percentages of the administered amount, either as active substance or as acetyl conjugate. In manure, these sulfonamides are persistent. Furthermore the acetyl conjugates are cleaved into the active sulfonamide during manure storage, possibly by nucleophilic attack of ammonium at the carbonyl carbon. Concentrations ranging from 0.1 to more than 10 mg sulfonamide/ kg liquid manure translate into loads of some few grams to several hundred grams per hectare per application that may reach agricultural soils. On a plot scale, losses of sulfonamide antibiotics by surface run-off have been reported to vary from 0.1 to 28% of the applied amount. One reason for this high variability might be the different irrigation intensities ranging from a few mm per day to 100mm/2h. In a field study carried out on a macroporous tile-drained clay soil relative losses of a sulfonamide antibiotic amounted to 0.48% and 0.01% in two subsequent years.

Competing with p-aminobenzoic acid in the enzymatic synthesis of dihydrofolic acid, sulfonamides inhibit the growth and reproduction of bacteria. Once released to the environment, sulfonamides distribute themselves among different environmental compartments, along with their degradation products, and are transported to surface water and groundwater. The physicochemical properties, the dosage applied and the nature of the environmental components with which they interact, govern the whole process. Sulfonamides, as a class, are only partially sorptive, non persistent, and leachable. They cannot be characterised as readily biodegradable. Their adsorption to soil increases with the aromaticity and electronegativity of functional groups attached to the sulfonyl phenyl amine core. Preferential flow in clay soils has been identified as a mechanism responsible for surface water contamination by sulfonamides.

George W. Ware et al: Reviews of Environmental Contamination and Toxicology Vol 187, 2006 pp 67-101.

Twelve different sulfonamides were selected for a biodegradation study using a respirometric screening test and an activated sludge simulation test. A simple bacterial growth inhibition test was applied to show that the sulfonamides did not affect the bacteria at the concentration levels used. None of the compounds were degraded in the screening test, leading to the conclusion that sulfonamides cannot be classified as readily biodegradable. In the simulation test, primary degradation of mixtures of four compounds at concentration levels of 250 to 500 µg/L were tested and analysed using high-performance liquid chromatography.

Biodegradation occurred after lag phases of 7 to 10 d at 20°C when nonadapted sludge was applied. Test compounds were degraded within a few days. At 6°C, degradation lag phases and degradation rates were three to four times longer. Sulfonamide adapted bacterial cultures were able to degrade either the same compounds as previously added or four other sulfonamides in a rapid and uniform way (t_{1/2} from 0.2 to 3 d). This finding shows that if capable of degrading one sulfonamide substance, these bacteria may also degrade many other sulfonamides. In practice, this implies that because the biodegradation rate is found to be identical for several sulfonamides in the sludge, the compounds may be assessed as a group by studying only a few compounds in applications such as environmental fate assessments. The mechanism for inducement of sulfonamide

continued...

LIQUID NITRATE TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-20
Version No:4
CD 2010/1 Page 13 of 14
Section 12 - ECOLOGICAL INFORMATION

adaptation to the bacteria was not revealed in this study.

Flemming Ingerslev and Bent Halling-Sørensen: Environmental Toxicology and Chemistry pp 2467-2473.
Laboratory tests showed that phototoxicity resulting from exposure to continuous UVB light generally increased the acute toxicity of the sulfonamides in *D. magna* by up to 2.3-fold. However, pulsed UVB exposure resulted in a greater increase in phototoxicity. Compared to fluorescent light only (no UVB), pulsed UVB irradiation (96 h) resulted in 12.0-, 5.8-, and 4.4-fold increases in toxicity for sulfamethazine, sulfathiazole, and sulfamethoxazole, respectively. This suggests that the mode of UV irradiation is more important than the dose (UV-intensity x exposure time) for the photo-enhancement of sulfonamide toxicity. Natural sunlight enhanced the toxicity of the sulfonamides to an even greater degree, likely because of the contribution of UVA light. This study suggests that without taking into account the effects of UV irradiation, it is possible to underestimate the actual consequences of phototoxic sulfonamide antibiotics in the aquatic environment.

Jinyong Jung et al: Earth and Environmental Science. Vol 17, January 2008, pp 37-45.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
polyethylene glycol	LOW		LOW	HIGH
sulfanilamide	HIGH		LOW	HIGH

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle where possible
Otherwise ensure that:
- licenced contractors dispose of the product and its container.
- disposal occurs at a licenced facility.

Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: DOT, IATA, IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

Regulations for ingredients

polyethylene glycol (CAS: 25322-68-3) is found on the following regulatory lists;

"GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "US - Minnesota Hazardous Substance List", "US Cosmetic Ingredient Review (CIR) Cosmetic ingredients found safe, with qualifications", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US DOT Coast Guard Bulk Hazardous Materials - List of Flammable and Combustible Bulk Liquid Cargoes", "US EPA High Production Volume Program Chemical List", "US FDA Indirect Food Additives: Adhesives and Components of Coatings - Substances for Use Only as Components of Adhesives - Adhesives", "US Food Additive Database", "US Inventory of Effective Food Contact Substance Notifications", "US Toxic Substances Control Act (TSCA) - Inventory"

sulfanilamide (CAS: 63-74-1) is found on the following regulatory lists;

"Canada Domestic Substances List (DSL)", "US DOE Temporary Emergency Exposure Limits (TEELs)", "US Toxic Substances Control Act (TSCA) - Inventory"

No data for Liquid Nitrate Test Solution #2 (CW: 4650-20)

continued...

LIQUID NITRATE TEST SOLUTION #2

Chemwatch GHS Safety Data Sheet
For Domestic Use Only.
Dec-23-2009
NC614TDP

CHEMWATCH 4650-20
Version No:4
CD 2010/1 Page 14 of 14

Section 16 - OTHER INFORMATION

Denmark Advisory list for selfclassification of dangerous substances

Substance	CAS	Suggested codes
sulfanilamide	63- 74- 1	R52/53

CONTACT

Mars Fishcare

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

For detailed advice on Personal Protective Equipment, refer to the following U.S. Regulations and Standards:

OSHA Standards - 29 CFR:

1910.132 - Personal Protective Equipment - General requirements

1910.133 - Eye and face protection

1910.134 - Respiratory Protection

1910.136 - Occupational foot protection

1910.138 - Hand Protection

Eye and face protection - ANSI Z87.1

Foot protection - ANSI Z41

Respirators must be NIOSH approved.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: Dec-23-2009

Print Date: May-20-2010